

+ IP 20



LOA

3 YRS

ldt



PHYSICAL DATA

FEATURES

- Material : Aluminium
- The FAVOR INM is an ideal option for anti-glare applications
- Adjustable
- DALI Dimming

OPTIONS & ACCESSORIES

- On/Off, Turnable White App, TRIAC Dimming options available for selection
- The FAVOR range offers a wide range of choices from narrow

to wide beam angles, pendants, recessed to surface mounted luminaires as well as track applications; offering different color finishes and accessory combinations

MOUNTING

Recessed

APPLICATION AREAS

Indoor, Commercial, Residential, Retail, Hospitality

TECHNICAL DATA


LF178812EDA

LAMP	LED
TOTAL POWER (W)	15W
SYSTEM OUTPUT (LM)	537LM
CCT (K)	2700 / 3000 / 4000K
CRI (Ra)	90
BEAM ANGLE	32° / 18°

OPERATING VOLTAGE-VAC	220-240V
SOURCE POWER (W)	13.9W
SOURCE OUTPUT (LM)	1465LM
CURRENT (MA)	100-700MA
DIMMING RANGE	1-100%
WEIGHT (KG)	0.35KG
DIMENSIONS	D:φ60 x H:135mm
CUT OUT	D:φ50mm



- CD / KLM
- C0 - C180
 - C90 - C270



E&OE MAY OCCUR



Lights By Linea
Since (1990)

Cape Town | 48 Marine Dr, Paarden Eiland | T: +27 21 511 6116
info@lightsbylinea.com | www.lightsbylinea.com