

+ IP 20



LOA

5 YRS

ldt



PHYSICAL DATA

FEATURES

- Material: Aluminium
- The FAVOR is an excellent choice for your lighting requirements; the range is great for accent lighting; with both narrow and wide beam angles. The range includes square and round recessed and surface mounted options, adjustable and rotatable options, pendant lights, surface spotlights as well as track applications
- Adjustable
- TRIAC dimmable

OPTIONS & ACCESSORIES

- On/Off, DALI and DIM 0/1-10V dimming options available
- Round, square and trimless options available
- Other CCT (K) and beam angles available for selection

MOUNTING: Recessed


APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail

TECHNICAL DATA

LF177912EDT

TOTAL POWER (W)	11.4W
SYSTEM OUTPUT (LM)	388LM
CCT (K)	3000K
CRI (Ra)	90
BEAM ANGLE	28°
OPERATING VOLTAGE-VAC	220-240V
CURRENT (MA)	350-700MA
DIMMING RANGE	30-100%
DIMENSIONS	D:Ø100 x 110mm
CUT OUT	D:Ø90mm



- CD / KLM
- C0 - C180
- C90 - C270

E&OE MAY OCCUR

