



- +IP 20
-
- 2 YRS

PHYSICAL DATA

FEATURES

- LED Bi-Pin
- Non-dimmable and dimmable options for selection

MOUNTING

as per lamp specifications

OPTIONS & ACCESSORIES

- Base available for selection: G9
- Dimmable 4W G9 Bi-Pin LED, G991WW, available for selection
- Dimmer modules available:
LED Trailing Edge Rotary Dimmer
LED Trailing Edge Push Button Dimmer

APPLICATION AREAS

Indoor, Commercial, Residential, Retail, Hospitality

TECHNICAL DATA

	G949WW	G949CW	G991WW
LAMP	LED	LED	LED
DIMMABLE	NO	NO	YES
BASE	G9	G9	G9
TOTAL POWER (W)	3W	3W	4W
SYSTEM OUTPUT (LM)	170LM	170LM	250LM
CCT (K)	3000K	4000K	3000K
CRI (RA)	70	70	70
BEAM ANGLE	360°	360°	360°
OPERATING VOLTAGE-VAC	230V	230V	230V
RATED LIFE (HRS)	15 000HRS	15 000HRS	15 000HRS
DIMENSIONS	D:φ16 X H:50.5mm	D:φ16 X H:50.5mm	D:φ16 X H:60mm

SHUTTLE DIM DATA

SDIM-L-LED-125/500

TYPE	BELL PRESS DIMMER
DIMMING METHOD	LEADING OR TRAILING EDGE
MIN LOAD POWER	125W and 500W
DIMENSIONS	125W: 36 x 36 x 12mm 500W: 42 x 42 x 13mm

