

PHYSICAL DATA

FEATURES

- Flame retardant ABS
- High output LED Panel
- Removable lens for easy cleaning
- Frosted Opal 80% transmission
- Prismatic Clear 90% transmission

- Control Tunable white - 2700K and 6500K optional
- Dimmable - Dali, 1-10v, DMX

MOUNTING

Recessed / Surface / Suspended with Suspension Kits

APPLICATION AREAS

Indoor, Commercial, Retail, Hospitality

OPTIONS & ACCESSORIES

- RGBW Colour changing optional


TECHNICAL DATA

GLF04 42W

GLF04 70W

LAMP	LED	LED
TOTAL POWER (W)	42W	70W
SYSTEM OUTPUT (LM)	5340LM	9900LM
EFFICACY (LM/W)	128	128
CCT (K)	3000 / 4000 / 5000K	3000 / 4000 / 5000K
CRI (Ra)	>80	>80
BEAM ANGLE	Wide Beam	Wide Beam
OPERATING VOLTAGE-VAC	220-240V	220-240V
OPERATING TEMP °C	-30°C TO 55°C	-30°C TO 55°C
RATED LIFE (HRS)	50 000HRS	50 000HRS
R9 VALUE	0.9	0.9
MAC ADAM STEP	3 SDCM	3 SDCM
DIMENSIONS	L:595 x W:595 x H:80mm	L:595 x W:595 x H:80mm

- CD / KLM
- C0 - C180
 - C90 - C270



E&OE MAY OCCUR

