

**PHYSICAL DATA**

**FEATURES**

- Self-encapsulated design
- High-quality PCB, high-thermal 3M adhesive
- Double layer FPC (2oz) for good heat dissipation
- 1-BIN delivery / 5m Reel
- Dimmable

**MOUNTING**

Surface

**APPLICATION AREAS**

Commercial, Offices, Industrial, Retail, Hotels, Schools, Restaurants, Museums, Galleries, Residential, Architectural, Supermarkets


**OPTIONS & ACCESSORIES**

- Offers six optional 2100-6000K
- Offers four optional R/G/B/Y colourful lights optional

**TECHNICAL DATA**

**LBLFLEX14.4CW24**

|                       |                       |
|-----------------------|-----------------------|
| LAMP                  | SMD2835               |
| OPERATING VOLTAGE-VAC | 24V                   |
| TOTAL POWER (W)       | 14.4W                 |
| SYSTEM OUTPUT (LM)    | 2154LM                |
| EFFICACY (LM/W)       | 90LM/W                |
| CCT (K)               | 4000K                 |
| CRI (Ra)              | >80                   |
| BEAM ANGLE            | 120°                  |
| RATED LIFE (HRS)      | 50 000                |
| CURRENT (MA)          | 0.6MA                 |
| TC CASE MAX TEMP (°C) | 60°C                  |
| MAC ADAM STEP         | 3 SDCM                |
| DIMENSIONS            | 5000mm x 10mm x 1.2mm |
| WEIGHT                | 0,25                  |
| CUT LENGTH            | 50mm/cut              |



E&OE MAY OCCUR

