

+ IP 20

LOA

✓ 5 YRS

ldt

FLX



PHYSICAL DATA

FEATURES

- Self encapsulated design
- High quality PCB, high thermal 3M adhesive
- Double layer FPC (2oz) for good heat dissipation
- 1-Bin delivery
- Dimmable

OPTIONS & ACCESSORIES

- Offers optional 1800-10000K
- White lights and R/G/B/Y colourful lights optional

MOUNTING

Surface


APPLICATION AREAS

Indoor, Commercial, Residential, Retail, Hospitality

TECHNICAL DATA

LBLFLEX9.6x24

LAMP	SMD3528
OPERATING VOLTAGE-VAC	24V
TOTAL POWER (W)	9.6W
SYSTEM OUTPUT (LM)	1008LM
EFFICACY (LM/W)	105LM/W
CCT (K)	3000 / 4000K
CRI (Ra)	>80
BEAM ANGLE	120°
RATED LIFE (HRS)	50 000HRS
CURRENT (MA)	0.4MA
TC CASE MAX TEMP (°C)	60°C
MAC ADAM STEP	3 SDCM
DIMENSIONS	5000mm x 8mm x 2mm
WEIGHT	0.25
CUT LENGTH	50mm/cut



cd/klm

C0 - C180

C90 - C270

E&OE MAY OCCUR

