

+ IP 20



LOA

3 YRS

ldt



PHYSICAL DATA

FEATURES

- Material: Aluminium
- It is a great choice for accent lighting in both residential and commercial spaces
- Rotatable and adjustable affords this luminaire great versatility

OPTIONS & ACCESSORIES

- DALI and ON/OFF options available
- 8W option available
- FAVOR INM available: D:Ø60 x H:135mm

- The FAVOR offers a wide range of choices from narrow to wide beam angles, from recessed to surface mounted and track applications; offering different color finishes and accessory combinations

MOUNTING

Recessed

APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail


TECHNICAL DATA

LF134712EDTWB

LAMP	LED
TOTAL POWER (W)	11W
SYSTEM OUTPUT (LM)	388LM
CCT (K)	3000K
CRI (Ra)	90
BEAM ANGLE	28° / 19°
OPERATING VOLTAGE-VAC	220-240V
CURRENT (MA)	500MA
FLICKER FACTOR	102.74HZ / 0.55%
WEIGHT	0,3KG
DIMENSIONS	D:Ø45 x 75mm
CUT OUT	D:Ø50mm



- cd/klm
- C0 - C180
- C90 - C270
- BEAM ANGLE



E&OE MAY OCCUR



LIGHTS BY LINEA

EST. 1990

DESIGN & TECHNICAL CERTAINTY