

+ IP  
54



LOA

✓  
5 YRS

ldt

### PHYSICAL DATA

#### FEATURES

- Material: Aluminium
- The PEBUK offers a simple streamlined design with an array of colours to choose from; ideal for any interior
- The Pebuk gives a soft and harmonious lighting effect and is anti-glare
- TRIAC Dimmable

#### MOUNTING

Surface

#### APPLICATION AREAS

Indoor, Commercial, Residential, Retail, Hospitality

#### OPTIONS & ACCESSORIES

- Turnable White App Dim function option available


### TECHNICAL DATA

### LF204812EDTWW

TOTAL POWER (W)	18.3W
SYSTEM OUTPUT (LM)	1087LM
CCT (K)	3000K
CRI (Ra)	90
BEAM ANGLE	36°
OPERATING VOLTAGE-VAC	220-240V
CURRENT (MA)	700MA
DIMMING RANGE	30-100%
FLICKER FACTOR	107.33HZ / 1.4%
WEIGHT (KG)	0.61KG
DIMENSIONS	D:Ø96 x L:100mm



- CD / KLM
- C0 - C180
  - C90 - C270



E&OE MAY OCCUR



LIGHTS BY  
**LINEA**

EST. 1990

DESIGN & TECHNICAL CERTAINTY