

- + IP 20**
- 
- LOA**
- 
- 3 YRS**
- ldt**

### PHYSICAL DATA

#### FEATURES

- Material : Aluminium
- The FLASH M V RO is a sleek and sophisticated luminaire is a perfect example of artistic and creative vision. With it's versatile modern minimalism, it can serve as an accent light, ambient or task light
- TRIAC Dimmable

#### OPTIONS & ACCESSORIES

- Driver: Smart Control - DIM by WIFI+BLE

The FLASH M V RO SENSOR with touch dim function is available for selection

- The FLASH M P SQ is available as suspended horizontal pendant in two length options
- The FLASH CK is available for the Ultra Track System

**MOUNTING:** Surface

#### APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail


### TECHNICAL DATA

### LF354012ETB

TOTAL POWER (W)	39W
SYSTEM OUTPUT (LM)	1476LM
CCT (K)	3000K
CRI (Ra)	90
BEAM ANGLE	180°
OPERATING VOLTAGE-VAC	100-240V
DIMMING RANGE	0-100%
ROD DIMENSIONS	D:Ø16 x H:1554mm
BASE DIMENSIONS	D:Ø45 x H:84mm
MOUNTING CUP	D:Ø30 x H:68mm



- CD / KLM
- C0 - C180
  - C90 - C270



E&OE MAY OCCUR



**LIGHTS BY**  
**LINEA**  
EST. 1990

DESIGN & TECHNICAL CERTAINTY