

+ IP 20



LOA

5 YRS

ldt

PHYSICAL DATA

FEATURES

- Material: Aluminium
- The CARD is dedicated to indoor corridors and staircases. Its unique linear light is formed through the specific angle of the light source passing through the hole in the cover creating a Trapezoid lighting effect
- Can be installed in cement and wooden walls
- Driver: On/Off

- Other CCT (K) available for selection
- The CARD is available in a rectangular and square option for selection
- Housing frame available for selection (LF001313)

MOUNTING

Recessed

APPLICATION AREAS


Indoor, Commercial, Residential, Hospitality, Retail

OPTIONS & ACCESSORIES

TECHNICAL DATA

LF450017AB

TOTAL POWER (W)	4W
SYSTEM OUTPUT (LM)	75LM
CCT (K)	3000K
CRI (Ra)	80
BEAM ANGLE	P(1*51°-57°)
OPERATING VOLTAGE-VAC	100-240V
CURRENT (MA)	700MA
HOUSING DIMENSIONS	W:130 x H:250 x D:52.5mm
DIMENSIONS	L:175 x W:35 x H:70mm
CUT OUT	165 x 30mm / 200 x 70mm



- CD / KLM
- C0 - C180
 - C90 - C270

E&OE MAY OCCUR



LIGHTS BY
LINEA
EST. 1990

DESIGN & TECHNICAL CERTAINTY