

- + IP 20
-
- LOA
- 3 YRS
- Idt

PHYSICAL DATA

FEATURES

- Material: cold pressed steel, powder coated
- Diffuser Lens creates even soft lighting

MOUNTING

Surface

APPLICATION AREAS


Indoor, Commercial, Retail, Hospitality

TECHNICAL DATA

	LLEDB1136	LLEDB1155	LLEDB1175
LAMP	LED	LED	LED
TOTAL POWER (W)	36W	55W	75W
SYSTEM OUTPUT	4000LM	6000LM	9500LM
EFFICACY (LM/W)	111	109	130
CCT (K)	4000K	4000K	4000K
CRI (RA)	80	80	≥80
BEAM ANGLE	120°	120°	120°
OPERATING VOLTAGE	220-240V	220-240V	220-240V
OPERATING TEMP °C	-20°C to 55°C	-20°C to 55°C	-20°C TO 50°C
RATED LIFE (HRS)	30 000 HRS	30 000 HRS	-20°C TO 40°C
CURRENT (MA)	290MA	370MA	370MA
LUMEN MAINTENANCE	L70B50	L70B50	L70B50
ILLUM @ 1M (LUX)	1191	1744	2735
POWER FACTOR	0.9	0.9	>0.9
R9 VALUE	13	13	10
UGR	>19	>19	>19
MAC ADAM STEP	1.3	2.5	2.5
WEIGHT (KG)	1.6KG	2KG	2.3KG
DIMENSIONS	L:1133 x W:63 x H:76mm	L:1415 x W:63 x H:76mm	L:1697 x W:63 x H:76mm

CD / KLM

- C0 - C180
- C90 - C270



E&OE MAY OCCUR

