

- +IP 65
- 3 YRS
-

PHYSICAL DATA

FEATURES

- Material: Die-cast aluminium (LM2) housing with stainless steel helicoils and a UV stable PMMA opal diffuser
- LED driver built in
- 1KV Surge Protection

- Side entry skirt available on request

MOUNTING

Surface

APPLICATION AREAS

Indoor, Outdoor, Commercial, Residential, Retail, Hospitality

OPTIONS & ACCESSORIES

- EMG 1hr or EMG 3hr available
- DALI, Occupancy Control, Daylight Harvesting, Time Switch Control and Bluetooth options available

TECHNICAL DATA


LLEDBH0215

LLEDBH0220

LAMP	LED	LED
TOTAL POWER (W)	11W	16W
SYSTEM OUTPUT (LM)	1585 / 1701LM	2162 / 2321LM
EFFICACY (LM/W)	148 / 159	137 / 147
CCT (K)	3000 / 4000K	3000 / 4000K
CRI (Ra)	>80	>80
BEAM ANGLE	120°	120°
OPERATING VOLTAGE-VAC	220-240V	220-240V
OPERATING TEMP °C	-20°C TO 45°C	-20°C TO 45°C
CURRENT (MA)	350MA	500MA
RATED LIFE (HRS)	50 000HRS	50 000HRS
POWER FACTOR	0.90	0.90
LUMEN MAINTENANCE	L70-B10	L70-B10
FLICKER FACTOR	<5%	<5%
MAC ADAM STEP	3 SDCM	3 SDCM
WEIGHT (KG)	1.35KG	1.35KG
DIMENSIONS	D:Ø276 x H:110mm	D:Ø276 x H:110mm

CD / KLM

- C0 - C180
- C90 - C270



E&OE MAY OCCUR

