



+IP  
66



5 YRS

ldt

### PHYSICAL DATA

#### FEATURES

- Lid is spun LM 6 aluminium – powder coated
- Base is glass filled nylon
- Lens is Macralon - PC
- Internally mounted control gear - Tridonic, Helvar or TCI

#### MOUNTING

Outdoor, Post-Top

#### APPLICATION AREAS

Outdoor, Group B Road Lighting, Recreational Spaces, Parks, Parking Areas

#### OPTIONS & ACCESSORIES

- Dali, 1-10V, DMX, Triac dimmable with correct gear
- 76mm diameter pole available


### TECHNICAL DATA

### LLEDPT02

LAMP	LED
TOTAL POWER (W)	28W
SYSTEM OUTPUT (LM)	4088LM
	Factor for loss through lens
EFFICACY (LM/W)	140
CCT (K)	3000 / 4000 / 5000K
CRI (Ra)	>80
BEAM ANGLE	SYMMETRICAL
OPERATING VOLTAGE-VAC	230V AC 50HZ
OPERATING TEMP °C	-20°C TO 40°C
RATED LIFE (HRS)	50 000 HRS
POWER FACTOR	>0,95
MAC ADAM STEP	3 SDCM
DIMENSIONS	D:φ473 x H:370mm
MOUNTING HEIGHT	3,5 TO 6M



- CD / KLM
- C0 - C180
  - C90 - C270



E&OE MAY OCCUR



**Lights By Linea**  
Since (1990)

Cape Town | 48 Marine Dr, Paarden Eiland | T: +27 21 511 6116  
info@lightsbylinea.com | www.lightsbylinea.com