

PHYSICAL DATA

FEATURES

- Material: Stainless steel, ABS end caps, anodised aluminium reflectors, powder coated or anodised aluminium gear channel
- Lens: 4mm Polycarbonate
- High efficiency LEDs
- 10KV surge arrestor standard
- No corrosive steel parts
- Mounting bracket for P2000 trunking or surface mounting to slab or from threaded rod

OPTIONS & ACCESSORIES

- Toughened glass lens type available on request
- 1-10V, DMX, DALI, KNX control protocols available
- Suspension kit, with clutch, available for easy suspension and height adjustment
- 90+ CRI, 2400K and 6500K available on request

MOUNTING: Surface


APPLICATION AREAS: Indoor, Commercial, Retail, Hospitality

TECHNICAL DATA


LLEDTB02

LAMP	LED
TOTAL POWER (W)	75W / 90W / 150W / 180W / 300W / 360W
SYSTEM OUTPUT (LM)	13200 / 15750 / 26400 / 31500 / 52800 / 63000 LM
EFFICACY (LM/W)	175
CCT (K)	3000 / 4000 / 5000K
CRI (Ra)	80
BEAM ANGLE	NARROW AND WIDE
OPERATING VOLTAGE-VAC	230V AC 50HZ
RATED LIFE (HRS)	50 000 HRS
FLICKER FACTOR	FLICKER FREE
R9 VALUE	0,9+
MAC ADAM STEP	3SDCM
SINGLE DIMENSIONS	L:510 x W:230 x 120mm
DOUBLE DIMENSIONS	L:1020 x W:480 x 120mm

NARROW



WIDE



CD / KLM

- C0 - C180
- C90 - C270

E&OE MAY OCCUR

