

Colour:  White

+IP  
65

✓  
5 YRS

ldt

### PHYSICAL DATA

#### FEATURES

- Material: Polycarbonate with stainless steel latches and mounting hangers
- Reflector is UV stable polycarbonate

#### MOUNTING

Surface

#### APPLICATION AREAS

Interior, Commercial, Residential, Hospitality, Retail

#### OPTIONS & ACCESSORIES

- DALI, DMX or 1-10V dimming function on request
- Available in three lengths: 660mm (2ft), 1277mm (4ft) and 1573mm (5ft)

### TECHNICAL DATA

#### LLEDVP0325W

#### LLEDVP0350W


#### LLEDVP0365W

#### LLEDVP0390W

LAMP	LED	LED	LED	LED
TOTAL POWER (W)	25W	50W	65W	90W
SYSTEM OUTPUT (LM)	3200LM	6400LM	8320LM	11000LM
EFFICACY (LM/W)	128	128	128	123
CCT (K)	3000 / 4000 / 5000K	3000 / 4000 / 5000K	3000 / 4000 / 5000K	3000 / 4000 / 5000K
CRI (Ra)	80	80	80	80
BEAM ANGLE	NARROW AND WIDE	NARROW AND WIDE	NARROW AND WIDE	NARROW AND WIDE
RATED LIFE (HRS)	50 000 HRS	50 000 HRS	50 000 HRS	50 000 HRS
OPERATING VOLTAGE-VAC	230VAC	230VAC	230VAC	230VAC
POWER FACTOR	>0.95	>0.95	>0.95	>0.95
R9 VALUE	0.9+	0.9+	0.9+	0.9+
MAC ADAM STEP	3SDCM	3SDCM	3SDCM	3SDCM
DIMENSIONS	W:101 x H:101 x L:660mm	W:101 x H:101 x L:1277mm	W:101 x H:101 x L:1277mm	W:101 x H:101 x L:1573mm

**NOTE:** If warm white 3000K is required – the lumen values will drop by 8%

CD / KLM  
 C0 - C180  
 C90 - C270



E&OE MAY OCCUR



**Lights By Linea**  
Since (1990)

Cape Town | 48 Marine Dr, Paarden Eiland | T: +27 21 511 6116  
 info@lightsbylinea.com | www.lightsbylinea.com