



+IP
65



LOA

5 YRS

ldt

PHYSICAL DATA

FEATURES

- Material: PC housing with PC diffuser
- Polycarbonate housing is cast from a single mold and therefore absolutely dust and waterproof
- High efficacy of up to 130-150lm/W to achieve energy saving
- PC opal diffuser achieved uniform light distribution
- 3 Power & CCT selectable available
- Highly durable and robust
- Dimming: On/Off DALI
- Lifetime: L80>100 000, L90>80 000

OPTIONS & ACCESSORIES

- Emergency/Motion sensor function available
- Length options: 600mm, 1200mm, 1500mm

MOUNTING

Suspension or Surface

APPLICATION AREAS

Indoor, Commercial, Residential, Retail, Parking area, Storage, Industrial, Leisure, Auto-showroom

TECHNICAL DATA

LLEDVP05405020

LAMP	LED
TOTAL POWER (W)	40W
SYSTEM OUTPUT (LM)	5200LM
EFFICACY (LM/W)	130 - 150LM/W
CCT (K)	3000K / 4000K / 5000K
CRI (Ra)	80
BEAM ANGLE	120°
OPERATING VOLTAGE-VAC	220 - 240V
OPERATING TEMP °C	-20°C TO 50°C
RATED LIFE (HRS)	50 000HRS L90 @ Tc=55°C
THD	<20%
MAC ADAM STEP	SDCM <3
DIMENSIONS	W:95 x L:1200 x H:80mm

E&OE MAY OCCUR



Lights by Linea
Since (1990)

Cape Town | T: +27 21 511 6116
info@lightsbylinea.com | www.lightsbylinea.com