

+ IP 20



LOA

5 YRS

ldt

F

PHYSICAL DATA

FEATURES

- Material: Aluminium / Iron
- Higher reflective efficiency with the ALANOD MIRO material

OPTIONS & ACCESSORIES

- Special CCT options available for the lighting of meat, bread, fish, vegetables and clothing
- Glass accessory available

MOUNTING

Suspended


APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail

TECHNICAL DATA

LP01225

TOTAL POWER (W)	30W x2
SYSTEM OUTPUT (LM)	2940 / 2970LM x2
EFFICACY (LM/W)	99
CCT (K)	3500 / 4000K
CRI (Ra)	80
BEAM ANGLE	15° / 24° / 44° / 59°
OPERATING VOLTAGE-VAC	220-240V
OPERATING TEMP °C	-20°C TO 50°C
SOURCE POWER (W)	25W x2
SOURCE OUTPUT (LM)	3417/ 3426LM x2
CURRENT (MA)	700MA x2
RATED LIFE (HRS)	50 000 HRS
ILLUM @ 1M (LUX)	21863 / 15892LX x2
FLICKER FACTOR	<4%
POWER FACTOR	≥0.9
R9 VALUE	12
UGR	<15
MAC ADAM STEP	3SDCM
DIMENSIONS	L:382 x W:228 x H:138mm



CD / KLM

- C0 - C180
- C90 - C270

E&OE MAY OCCUR

