



- + IP 20
- 
- LOA**
- 5 YRS
- 

**PHYSICAL DATA**

**FEATURES**

- Material: Aluminium and polycarbonate

**MOUNTING**

Suspended

**OPTIONS & ACCESSORIES**

- TRIAC, 0-10V, Dali dimming options available
- Surface Mount, Recessed versions available

**APPLICATION AREAS**

Indoor, Commercial, Residential, Hospitality, Retail

**TECHNICAL DATA**

	LP0632	LP0636	LP0672
TOTAL POWER (W)	32W	32W	66W
SYSTEM OUTPUT (LM)	3357 / 3368LM	3468 / 3529LM	7350 / 7577LM
EFFICACY (LM/W)	97 / 101	102 / 105	107 / 115
CCT (K)	3500 / 4000K	3500 / 4000K	3500 / 4000K
CRI (Ra)	80	80	80
BEAM ANGLE	108°	108°	112°
OPERATING VOLTAGE-VAC	220-240V	220-240V	220-240V
OPERATING TEMP °C	-20°C TO 50°C	-20°C TO 50°C	-20°C TO 50°C
SOURCE POWER (W)	50 000 HRS	50 000 HRS	50 000 HRS
SOURCE OUTPUT (LM)	31W	30W	60W
CURRENT (MA)	700MA	700MA	700MA
RATED LIFE (HRS)	4225 / 4229LM	4359 / 4435LM	8150 / 8100LM
ILLUM @ 1M (LUX)	428 / 430LX	455 / 451LX	759 / 793LX
FLICKER FACTOR	<4%	<4%	<4%
POWER FACTOR	≥0.9	≥0.9	≥0.9
R9 VALUE	11	11	11
UGR	<25	<25	<25
MAC ADAM STEP	3SDCM	3SDCM	3SDCM
DIMENSIONS	D:Ø350 x H:97mm	D:Ø480 x H:100mm	D:Ø680 x H:100mm

