

+ IP 20



LOA

5 YRS

ldt

F

**PHYSICAL DATA**

**FEATURES**

- Material: Die-cast aluminium housing / trim ring
- Powder coated trim ring
- Higher reflective efficiency with the Alanrod Miro material

- EMG pack available

**MOUNTING**

Recessed

**OPTIONS & ACCESSORIES**

- TRIAC, 0-10V and DALI Dimming available
- Glass accessory available
- Special CCT available for meat, bread, fish, vegetables and clothing

**APPLICATION AREAS**


Indoor, Commercial, Residential, Hospitality, Retail

**TECHNICAL DATA**

**LRD0406**

**LRD0412**

TOTAL POWER (W)	7W	12W
SYSTEM OUTPUT (LM)	629LM	1694LM
EFFICACY (LM/W)	70	72
CCT (K)	4000K	4000K
CRI (Ra)	80	80
BEAM ANGLE	28° / 53°	28°
OPERATING VOLTAGE-VAC	220 - 240V	220 - 240V
CURRENT (MA)	200MA	350MA
RATED LIFE (HRS)	50 000 HRS	50 000 HRS
FLICKER FACTOR	<4%	<4%
POWER FACTOR	≥0.9	≥0.9
R9 VALUE	11	12
UGR	<7	<7
MAC ADAM STEP	3SDCM	3SDCM
DIMENSIONS	D:Ø85 x H:105mm	D:Ø85 x H:105mm
CUT OUT	D:Ø75mm	D:Ø75mm



CD / KLM

- C0 - C180
- C90 - C270

E&OE MAY OCCUR

