

+ IP 20



LOA

5 YRS

ldt

F



PHYSICAL DATA

FEATURES

- Material: Die-cast aluminium housing / trim ring
- Powder coated trim ring
- Higher reflective efficiency with the Alanrod Miro material
- Adjustable

MOUNTING

Recessed

APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail

OPTIONS & ACCESSORIES

- TRIAC, 0-10V and DALI Dimming available
- Glass accessory available

TECHNICAL DATA


LRD0506

LRD0512

TOTAL POWER (W)	7W	15W
SYSTEM OUTPUT (LM)	519 / 695 / 651LM	1051 / 1112 / 1195LM
EFFICACY (LM/W)	70 / 78 / 77	69 / 72 / 79
CCT (K)	3000 / 3500 / 4000K	3000 / 3500 / 4000K
CRI (Ra)	80	80
BEAM ANGLE	20° / 35°	20° / 35°
OPERATING VOLTAGE-VAC	220-240V	220-240V
OPERATING TEMP °C	-20°C TO 50°C	-20°C TO 50°C
SOURCE POWER (W)	6W	12W
SOURCE OUTPUT (LM)	716 / 915 / 961LM	1406 / 1635 / 1652LM
CURRENT (MA)	200MA	350MA
RATED LIFE (HRS)	50 000 HRS	50 000 HRS
ILLUM @ 1M (LUX)	1129 / 1700 / 1584LX	2625 / 2532 / 2815LX
FLICKER FACTOR	<4%	<4%
POWER FACTOR	≥0.9	≥0.9
R9 VALUE	11	12
UGR	<22	<22
MAC ADAM STEP	3SDCM	3SDCM
DIMENSIONS	D:Ø85 x H:100mm	D:Ø85 x H:100mm
CUT OUT	D:Ø75mm	D:Ø75mm

CD / KLM

- C0 - C180
- C90 - C270



E&OE MAY OCCUR

