

+ IP 20



LOA

5 YRS

ldt

F



PHYSICAL DATA

FEATURES

- Material: Aluminium
- Luminaire comes with the simple tilting construction and design
- Anti-glare device, providing visual comfort light and lights walls/objects uniformly
- Adjustable

- TRIAC, 0-10V, Dali dimming options available
- Straight or slant versions available for wide or narrow beam angle

MOUNTING

Recessed

APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail

OPTIONS & ACCESSORIES

- Other CCT (K) available
- Glass accessory available

TECHNICAL DATA


LRD0806

LRD0812

TOTAL POWER (W)	7W	15W
SYSTEM OUTPUT (LM)	423 / 432LM	767 / 779LM
EFFICACY (LM/W)	50 / 51	51 / 52
CCT (K)	3500 / 4000K	3500 / 4000K
CRI (Ra)	80	80
BEAM ANGLE	34°	36° / 34°
OPERATING VOLTAGE-VAC	220-240V	220-240V
OPERATING TEMP °C	-20°C TO 50°C	-20°C TO 50°C
SOURCE POWER (W)	6W	12W
SOURCE OUTPUT (LM)	915 / 961LM	1652LM
CURRENT (MA)	200MA	350MA
RATED LIFE (HRS)	50 000 HRS	50 000 HRS
ILLUM @ 1M (LUX)	286 / 301LX	581 / 548LX
FLICKER FACTOR	<4%	<4%
POWER FACTOR	≥0.9	≥0.9
R9 VALUE	11	12
UGR	<7	<7
MAC ADAM STEP	3SDCM	3SDCM
DIMENSIONS	D:Ø87 x H:111mm	D:Ø87 x H:111mm
CUT OUT	D:Ø75mm	D:Ø75mm

CD / KLM

- C0 - C180
- C90 - C270



E&OE MAY OCCUR

