

+IP
20



LOA

✓
5 YRS

ldt

F

PHYSICAL DATA

FEATURES

- Material: Aluminium
- Designed with the narrowest trim making it as close to trimless as possible but without the install difficulty of trimless
- Higher reflective efficiency with the Alanrod Miro material

OPTIONS & ACCESSORIES

- CRI82, CRI93 and CRI97 available
- Special CCT available for meat, bread, fish, vegetables and clothing

- Flex and plug or direct connection options available
- TRIAC, 0-10V, Dali dimming options available

MOUNTING

Recessed

APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail


TECHNICAL DATA

LRD09

TOTAL POWER (W)	30W
SYSTEM OUTPUT (LM)	2724LM
CCT (K)	3000K
CRI (Ra)	90
BEAM ANGLE	24° / 31° / 60°
OPERATING VOLTAGE-VAC	220 - 240V
CURRENT (MA)	700MA
RATED LIFE (HRS)	50 000HRS
FLICKER FACTOR	<4%
POWER FACTOR	≥0.9
R9 VALUE	11
UGR	<15
MAC ADAM STEP	3SDCM
DIMENSIONS	D:Ø165 x H:155mm
CUT OUT	D:Ø155mm

CD / KLM

- C0 - C180
- C90 - C270



E&OE MAY OCCUR

