

+ IP 20



LOA

5 YRS

ldt

F

30°

PHYSICAL DATA

FEATURES

- Material: Aluminium
- Powder coated trim ring
- Higher reflective efficiency with the Alanrod Miro material
- Adjustable

MOUNTING

Recessed

APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail

OPTIONS & ACCESSORIES


- Other CCT (K) available
- Glass accessory available
- TRIAC, 0-10V, Dali dimming options available

TECHNICAL DATA

LRD1025

LRD1033

TOTAL POWER (W)	30W	36W
SYSTEM OUTPUT (LM)	2940 / 2970LM	3527 / 3486LM
EFFICACY (LM/W)	99	95 / 94
CCT (K)	3500 / 4000K	3500 / 4000K
CRI (Ra)	80	80
BEAM ANGLE	10° / 24° / 42° / 64°	10° / 24° / 42° / 64°
OPERATING VOLTAGE-VAC	220-240V	220-240V
OPERATING TEMP °C	-20°C TO 50°C	-20°C TO 50°C
SOURCE POWER (W)	25W	33W
SOURCE OUTPUT (LM)	3417 / 3426LM	4135 / 4048LM
CURRENT (MA)	700MA	900MA
RATED LIFE (HRS)	50 000 HRS	50 000 HRS
ILLUM @ 1M (LUX)	21863 / 15892LX	26248 / 18458LX
FLICKER FACTOR	<4%	<4%
POWER FACTOR	≥0.9	≥0.9
R9 VALUE	12	12
UGR	<22	<22
MAC ADAM STEP	3SDCM	3SDCM
DIMENSIONS	D:Ø180 x H:110mm	D:Ø180 x H:110mm
CUT OUT	D:Ø170mm	D:Ø170mm



CD / KLM

- C0 - C180
- C90 - C270

E&OE MAY OCCUR

