

+ IP 20



LOA

5 YRS

ldt

F

PHYSICAL DATA

FEATURES

- Material: Aluminium and polycarbonate diffuser
- Anti-glare design
- Better heat dissipation with higher density aluminium alloy

OPTIONS & ACCESSORIES

- Flex and plug or direct connection options available
- TRIAC, 0-10V, Dali dimming options available

MOUNTING

Recessed

APPLICATION AREAS


Indoor, Commercial, Residential, Hospitality, Retail

TECHNICAL DATA

LRD114

TOTAL POWER (W)	3W x4
SYSTEM OUTPUT (LM)	676LM x4
EFFICACY (LM/W)	49
CCT (K)	3000K
CRI (Ra)	80
BEAM ANGLE	13°
OPERATING VOLTAGE-VAC	220-240V
OPERATING TEMP °C	-20°C TO 50°C
SOURCE POWER (W)	4 x 2W
SOURCE OUTPUT (LM)	812LM x4
CURRENT (MA)	700MA x4
RATED LIFE (HRS)	50 000 HRS
ILLUM @ 1M (LUX)	1334LX x4
FLICKER FACTOR	<4%
POWER FACTOR	≥0.9
R9 VALUE	11
UGR	<7
MAC ADAM STEP	3SDCM
DIMENSIONS	L:138 x W:44 x H:39mm
CUT OUT	130 x 38mm

Single Beam



CD / KLM

C0 - C180

C90 - C270

E&OE MAY OCCUR



Lights By Linea
Since (1990)

Cape Town | 48 Marine Dr, Paarden Eiland | T: +27 21 511 6116
info@lightsbylinea.com | www.lightsbylinea.com