

+ IP 20



LOA



ldt



PHYSICAL DATA

FEATURES

- Material: Aluminium
- The traditional commercial lighting fitting
- Higher reflective efficiency with the Alanrod Miro material
- Adjustable

OPTIONS & ACCESSORIES

- TRIAC, 0-10V, Dali dimming options available
- Special CCT available for meat, bread, fish, vegetables and clothing

- Lens options available

MOUNTING

Recessed

APPLICATION AREAS


Indoor, Commercial, Residential, Hospitality, Retail

TECHNICAL DATA

LRD12225

| | |
|-----------------------|-------------------------------|
| TOTAL POWER (W) | 30W x2 |
| SYSTEM OUTPUT (LM) | 2841 / 2940 / 2970LM (x 2) |
| EFFICACY (LM/W) | 95 / 99 / 99 |
| CCT (K) | 3000 / 3500 / 4000K |
| CRI (Ra) | 80 |
| BEAM ANGLE | 10° / 24° / 42° / 64° |
| OPERATING VOLTAGE-VAC | 220-240V |
| OPERATING TEMP °C | -20°C TO 50°C |
| SOURCE POWER (W) | 25W x2 |
| SOURCE OUTPUT (LM) | 3201 / 3417 / 3426LM (x 2) |
| CURRENT (MA) | 900MA (x2) |
| RATED LIFE (HRS) | 50 000 HRS |
| ILLUM @ 1M (LUX) | 15224 / 21863 / 15892LX (x 2) |
| FLICKER FACTOR | <4% |
| POWER FACTOR | ≥0.9 |
| R9 VALUE | 12 |
| UGR | <22 |
| MAC ADAM STEP | 3SDCM |
| DIMENSIONS | L:176 x W:176 x H:138mm |
| CUT OUT | 325 x 165mm |

Single 14° Beam Angle



CD / KLM

C0 - C180

C90 - C270

E&OE MAY OCCUR



Lights By Linea
Since (1990)

Cape Town | 48 Marine Dr, Paarden Eiland | T: +27 21 511 6116
info@lightsbylinea.com | www.lightsbylinea.com