

+ IP 20



LOA

5 YRS

ldt

F



PHYSICAL DATA

FEATURES

- Material: Aluminium
- The body can be recessed into the ceiling
- Adjustable and extractable
- Higher reflective efficiency with the Alanrod Miro material

- Lens options available

MOUNTING

Recessed

APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail

OPTIONS & ACCESSORIES

- TRIAC, 0-10V, Dali dimming options available
- Special CCT available for meat, bread, fish, vegetables and clothing


TECHNICAL DATA

LRD14225

LRD14233

| | | |
|-----------------------|----------------------------|----------------------------|
| TOTAL POWER (W) | 30W x2 | 36W x2 |
| SYSTEM OUTPUT (LM) | 2841 / 2940 / 2970LM (x2) | 3204 / 3527 / 3486LM (x2) |
| EFFICACY (LM/W) | 95 / 99 / 99 | 86 / 95 / 94 |
| CCT (K) | 3000 / 3500 / 4000K | 3000 / 3500 / 4000K |
| CRI (Ra) | 80 | 80 |
| BEAM ANGLE | 10° / 24° / 42° / 64° | 10° / 24° / 42° / 64° |
| OPERATING VOLTAGE-VAC | 220-240V | 220-240V |
| OPERATING TEMP °C | -20°C TO 50°C | -20°C TO 50°C |
| SOURCE POWER (W) | 25W x2 | 33W x2 |
| SOURCE OUTPUT (LM) | 3201 / 3417 / 3426LM (x2) | 3851 / 4135 / 4048LM (x2) |
| CURRENT (MA) | 500MA (x2) | 900MA (x2) |
| RATED LIFE (HRS) | 50 000 HRS | 50 000 HRS |
| ILLUM @ 1M (LUX) | 15224/21863/15892LX (x2) | 17410/26248/18458LX (x2) |
| FLICKER FACTOR | <4% | <4% |
| POWER FACTOR | ≥0.9 | ≥0.9 |
| R9 VALUE | 11 | 12 |
| UGR | <22 | <22 |
| MAC ADAM STEP | 3SDCM | 3SDCM |
| DIMENSIONS | D:Ø116.5 x H:171 x W:335mm | D:Ø116.5 x H:171 x W:335mm |
| CUT OUT | 300 x 180mm | 300 x 180mm |

Single Beam Angle



CD / KLM

- C0 - C180
- C90 - C270

E&OE MAY OCCUR



Lights By Linea
Since (1990)

Cape Town | 48 Marine Dr, Paarden Eiland | T: +27 21 511 6116
info@lightsbylinea.com | www.lightsbylinea.com