

- +IP 20
-
- LOA
- 5 YRS

PHYSICAL DATA

FEATURES

- Material: Aluminium
- Better heat dissipation with higher density aluminium alloy
- Higher reflective efficiency with the ALANOD MIRO material
- Complete with driver
- Adjustable

OPTIONS & ACCESSORIES

- Cross, Barn Door, Honeycomb louver, Wall-washer and Glass accessories available

TRIAC / DALI Dimming available

Special CCT options available for the lighting of meat, bread, fish, vegetables and clothing

Single and double light fixture available for selection

MOUNTING
Recessed


APPLICATION AREAS
Indoor, Commercial, Residential, Hospitality, Retail

- Idt
- F
- 70°
- 355°

TECHNICAL DATA LRD153

TOTAL POWER (W)	40W
SYSTEM OUTPUT (LM)	4119LM
EFFICACY (LM/W)	95LM/W
CCT (K)	3000K
CRI (Ra)	80
BEAM ANGLE	37°
OPERATING VOLTAGE-VAC	220 - 240V
SOURCE OUTPUT (LM)	4614LM
CURRENT (MA)	700MA
RATED LIFE (HRS)	50 000HRS L70
ILLUM @ 1M (LUX)	6007LUX (Single Head)
FLICKER FACTOR	<4%
POWER FACTOR	0.97
R9 VALUE	58
UGR	24
MAC ADAM STEP	3 SDCM
WEIGHT (KG)	10.84KG
DIMENSIONS	L:414 x H:112.1mm
CUT OUT	L:400 x W:140mm

SINGLE BEAM



- CD / KLM
- C0 - C180
 - C90 - C270

E&OE MAY OCCUR

