

+ IP 20



LOA

5 YRS

ldt

F



PHYSICAL DATA

FEATURES

- Material: Aluminium
- Better heat dissipation with higher density aluminium alloy
- Higher reflective efficiency with the ALANOD MIRO material
- Adjustable

OPTIONS & ACCESSORIES

- Cross, Barn Door, Honeycomb louver, Wall-washer and Glass accessories available
- TRIAC / DALI Dimming available

- Special CCT options available for the lighting of meat, bread, fish, vegetables and clothing
- Double and triple light fixture available

MOUNTING

Recessed

APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail

TECHNICAL DATA


LRD15

TOTAL POWER (W)	20W
SYSTEM OUTPUT (LM)	1788 / 1937LM
EFFICACY (LM/W)	86 / 93
CCT (K)	3500 / 4000K
CRI (Ra)	80
BEAM ANGLE	21°
OPERATING VOLTAGE-VAC	220-240V
OPERATING TEMP °C	-20°C TO 50°C
SOURCE POWER (W)	17W
SOURCE OUTPUT (LM)	2443 / 2480LM
CURRENT (MA)	500MA
RATED LIFE (HRS)	50 000 HRS
ILLUM @ 1M (LUX)	4585 / 4948LX
FLICKER FACTOR	<4%
POWER FACTOR	≥0.9
R9 VALUE	11
UGR	<7
MAC ADAM STEP	3SDCM
DIMENSIONS	D:Ø80 x L:95mm
CUT OUT	L:140 x W:140mm

CD / KLM

C0 - C180

C90 - C270



E&OE MAY OCCUR



Lights By Linea
Since (1990)

Cape Town | 48 Marine Dr, Paarden Eiland | T: +27 21 511 6116
info@lightsbylinea.com | www.lightsbylinea.com