



Cut Out: Ø76mm



+IP
54



LOA

✓
3 YRS



PHYSICAL DATA

FEATURES

- Extruded aluminium housing with no external screws
- Electrostatic powder coating
- Optional anti-glare accessories
- Simple lamp installation

OPTIONS & ACCESSORIES

- Dali / DSI dimmable gear available

MOUNTING

Recessed Downlight

APPLICATION AREAS

Hospitality, Restaurants, Residential, Gallery

TECHNICAL DATA

LRD52

| | |
|-------------|----------------|
| LAMP HOLDER | GU10 |
| VOLTAGE | 230V 50Hz |
| DIMENSIONS | D:Ø85 x H:44mm |
| CUT OUT | Ø76mm |

LAMP DATA

LPPAR165036

| | |
|-----------------------|-----------------------|
| LAMP | LED |
| DIMMABLE | YES |
| BASE | GU10 |
| TOTAL POWER (W) | 5.5W |
| SYSTEM OUTPUT (LM) | 380LM / 400LM |
| CCT (K) | 3000K / 4000K / 6500K |
| CRI (Ra) | 90 |
| BEAM ANGLE | 36° |
| OPERATING VOLTAGE-VAC | 220-240V |
| RATED LIFE (HRS) | 25 000HRS |
| DIMENSIONS | D:Ø51 x H:52mm |



PLEASE NOTE:

Lamp specifications and lamp warranties may differ



LIGHTS BY
LINEA

EST. 1990

DESIGN & TECHNICAL CERTAINTY

E&OE MAY OCCUR