

- +IP 20
- 
- LOA**
- 5 YRS
- 

### PHYSICAL DATA

#### FEATURES

- Material: White powder-coated aluminium with polycarbonate diffuser with silver-finish reflector
- Stainless steel spring clips
- Very low glare with UGR <19 (20W & 28W) or UGR <22 (10W & 15W)
- Complete with total length of 0.83m of flex and SWIFT connector
- Fast, simple and efficient installability
- Non-dimmable

- Suitable for switching by PIR, Microwave or Photocell

#### FEATURES

- Suitable for use with the ROBUS R3EMPK4-PSU plug and play Emergency Pack

**MOUNTING:** Recessed

#### APPLICATION AREAS

Indoor, Commercial, Retail, Hospitality, Public Buildings

### TECHNICAL DATA

#### LRD55104031


#### LRD55154031

#### LRD55204031

#### LRD55284031

LAMP	LED	LED	LED	LED
TOTAL POWER (W)	10.5W	13.7W	20W	28W
SYSTEM OUTPUT (LM)	1030LM	1380LM	1850LM	2740LM
EFFICACY (LM/W)	98	101	93	96
CCT (K)	4000K	4000K	4000K	4000K
CRI (RA)	80	80	80	80
BEAM ANGLE	50°	50°	50°	50°
OPERATING VOLTAGE-VAC	220-240V	220-240V	220-240V	220-240V
RATED LIFE (HRS)	50 000HRS	50 000HRS	50 000HRS	50 000HRS
ILLUM @ 1M (LUX)	1300LX	1580LX	2580LX	3570LX
POWER FACTOR	0.9	0.9	0.95	0.95
UGR	<22	<22	<19	<19
MAC ADAM STEP	6SDCM	6SDCM	6SDCM	6SDCM
OPERATING TEMP °C	-20°C to +40°C	-20°C to +40°C	-20°C to +40°C	-20°C to +40°C
WEIGHT (KG)	0.25KG	0.30KG	0.35KG	0.5KG
DIMENSIONS	D:φ113 x H:68mm	D:φ145 x H:82mm	D:φ174 x H:90mm	D:φ232 x H:118mm
CUT OUT	D:φ90-102mm	D:φ120-130mm	D:φ145mm	D:φ195mm

- CD / KLM
- C0 - C180
  - C90 - C270



E&OE MAY OCCUR

