



+IP
44



LOA

✓
5 YRS

ldt

F

PHYSICAL DATA

FEATURES

- Material: Aluminium
- Optical system: Lens UGR<19
- LED source: Bridgelux COB
- Driver: LED TRAIIC dimmable

OPTIONS & ACCESSORIES

- Curved - paint white/ electroplating black
- Straight - paint white/ electroplating black

MOUNTING

Recessed

APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail

TECHNICAL DATA

LRD7307303631

LAMP	COB
TOTAL POWER (W)	7W
SYSTEM OUTPUT (LM)	770LM
EFFICACY (LM/W)	100LM/W
CCT (K)	3000K
CRI (Ra)	90
BEAM ANGLE	36°
OPERATING VOLTAGE-VAC	200 - 240V
OPERATING TEMP °C	-10°C TO 45°C
CURRENT (MA)	300MA
RATED LIFE (HRS)	50 000HRS
UGR	<19
DIMENSIONS	D:Ø63 x H:45mm
CUT OUT	Ø55mm



E&OE MAY OCCUR



Lights by Linea
Since (1990)

Cape Town | T: +27 21 511 6116
info@lightsbylinea.com | www.lightsbylinea.com