

- + IP 20
- LOA
- 5 YRS
- ldt

### PHYSICAL DATA

#### FEATURES

- Material: Aluminium
- Heatsink and driver integrated in the housing of luminaire

#### MOUNTING

Surface

#### OPTIONS & ACCESSORIES

- TRIAC, 0-10V, Dali dimming options available
- Special CCT available for meat, bread, fish, vegetables and clothing available
- Lens options available
- Pendant option available

#### APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail


### TECHNICAL DATA

#### LSD0117

#### LSD0125

TOTAL POWER (W)	20W	30W
SYSTEM OUTPUT (LM)	1974 / 2245LM	2867 / 2970LM
EFFICACY (LM/W)	95 / 108	97 / 99
CCT (K)	3500 / 4000K	3500 / 4000K
CRI (Ra)	80	80
BEAM ANGLE	15° / 24° / 44° / 59°	15° / 24° / 44° / 59°
OPERATING VOLTAGE-VAC	220-240V	220-240V
OPERATING TEMP °C	-20°C TO 50°C	-20°C TO 50°C
SOURCE POWER (W)	17W	25W
SOURCE OUTPUT (LM)	2448 / 2479LM	3417 / 3426LM
CURRENT (MA)	500MA	700MA
RATED LIFE (HRS)	50 000 HRS	50 000 HRS
ILLUM @ 1M (LUX)	10401 / 11743LX	15413 / 15892LX
FLICKER FACTOR	<4%	<4%
POWER FACTOR	≥0.9	≥0.9
R9 VALUE	11	12
UGR	<15	<15
MAC ADAM STEP	3SDCM	3SDCM
DIMENSIONS	D:117 x H:176mm	D:117 x H:176mm

#### 16° Beam Angle



- CD / KLM
- C0 - C180
  - C90 - C270

E&OE MAY OCCUR

