

- + IP 20
-
-
-
-
-

PHYSICAL DATA

FEATURES

- Material: Aluminium and polycarbonate
- Flood LED panel light

OPTIONS & ACCESSORIES

- Pendant, Recessed versions available
- TRIAC, 0-10V, Dali dimming options available

MOUNTING

Surface

APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail


TECHNICAL DATA

LSD0932

LSD0966

TOTAL POWER (W)	32W	66W
SYSTEM OUTPUT (LM)	3468 / 3529LM	7250 / 7577LM
EFFICACY (LM/W)	108 / 105	107 / 115
CCT (K)	3500 / 4000K	3500 / 4000K
CRI (Ra)	80	80
BEAM ANGLE	108°	111°
OPERATING VOLTAGE-VAC	220-240V	220-240V
OPERATING TEMP °C	-20°C TO 50°C	-20°C TO 50°C
SOURCE POWER (W)	30W	60W
SOURCE OUTPUT (LM)	4359 / 4435LM	8150 / 8100LM
CURRENT (MA)	700MA	1400MA
RATED LIFE (HRS)	50 000 HRS	50 000 HRS
ILLUM @ 1M (LUX)	455 / 451LX	759 / 793LX
FLICKER FACTOR	<4%	<4%
POWER FACTOR	≥0.9	≥0.9
R9 VALUE	11	17
UGR	<25	<25
MAC ADAM STEP	3SDCM	3SDCM
DIMENSIONS	D:Ø480 x H:100mm	D:Ø680 x H:100mm

- CD / KLM
- C0 - C180
 - C90 - C270



E&OE MAY OCCUR

