



-  +IP 20
- 
-  LOA
-  5 YRS
-  ldt

PHYSICAL DATA

FEATURES

- Material: Aluminum with PMMA diffuser
- Modular structure, easy for driver replacement
- 1.5mm profile thickness
- Available in single and continuous linear, easy for connection & maintenance
- CCT selectable
- Dimming: On/Off DALI
- Magnetic uplight module

- Available in 3 lengths: 1200mm / 1500mm / 3000mm
- Direct lighting wattages: 25W / 30W / 60W
- Indirect lighting wattages: 35W / 45W / 90W
- Aluminum end cap

MOUNTING

Surface or Suspended

APPLICATION AREAS

Indoor, Commercial, Residential, Retail

OPTIONS & ACCESSORIES

- Suspension accessories and extra 2.4m rollable diffuser

TECHNICAL DATA

LSL13352CCT

LAMP	LED
TOTAL POWER (W)	35W
SYSTEM OUTPUT (LM)	4500LM
EFFICACY (LM/W)	130LM/W
CCT (K)	3000K / 4000K / 5000K
CRI (Ra)	90
BEAM ANGLE	110° DOWN 120° UP
OPERATING VOLTAGE-VAC	220 - 240V
OPERATING TEMP °C	-20°C To 40°C
RATED LIFE (HRS)	50 000HRS L90B10
THD	<20%
MAC ADAM STEP	SDCM <3
WEIGHT (KG)	3.5KG
DIMENSIONS	W:60 x L:1200 x H:80mm

