



PHYSICAL DATA

FEATURES

- Material: Aluminum with PMMA diffuser
- Modular structure, easy for driver replacement
- Efficacy: >130lm/W@ opal, >140lm/W@MPD
- Available in single and continuous linear, easy for connection & maintenance
- CCT selectable
- Dimming: On/Off DALI

OPTIONS & ACCESSORIES

- Suspension accessories and extra 2.4m rollable diffuser
- CCT: 3000K / 4000K / 5000K fixed or 2/3 CCT selectable

- Recessed mounting clip
- Available in 3 lengths: 1200mm / 1500mm / 3000mm
- Direct lighting wattages: 22W / 27W / 55W
- Indirect lighting wattages: 32W / 40W / 80W

MOUNTING

Recessed

APPLICATION AREAS

Indoor, Commercial, Residential, Retail

TECHNICAL DATA

LSL09234031

LAMP	LED
TOTAL POWER (W)	32W
SYSTEM OUTPUT (LM)	4500LM
EFFICACY (LM/W)	130LM/W
CCT (K)	4000K
CRI (Ra)	90
BEAM ANGLE	110°
OPERATING VOLTAGE-VAC	220 - 240V
OPERATING TEMP °C	-20°C To 40°C
RATED LIFE (HRS)	100 000HRS L80 80 000HRS L90
THD	<20%
MAC ADAM STEP	SDCM <3
DIMENSIONS	W:60 x L:1200 x H:80mm

E&OE MAY OCCUR



Lights by Linea
Since (1990)

Cape Town | T: +27 21 511 6116
info@lightsbylinea.com | www.lightsbylinea.com