

- +IP 20**
-
- LOA**
-
- 5 YRS**
- ldt**

PHYSICAL DATA

FEATURES

- Material: Aluminum
- CCT Selectable
- Modular structure, easy for driver replacement
- Available in a single and continuous linear
- Easy for connection & maintenance
- Magnetic uplight module
- Dimming: On/off DALI
- Up & downlight distribution ration is adjustable
- Beam angle: Opal 110° down | 120° up
MPD 9° down | 120° up, Brightview UGR film

OPTIONS & ACCESSORIES

- Suspension accessories
- Available in 3 lengths: 1200mm / 1500mm / 3000mm
- Direct lighting wattages: 30W / 40W / 80W
- Indirect lighting wattages: 40W / 50W / 100W

MOUNTING

Surface and Suspended

APPLICATION AREAS


Indoor, Commercial, Offices, Banks, Schools, Retail

TECHNICAL DATA

LSL104CCT31

| | |
|--------------------|------------------------|
| LAMP | LED |
| TOTAL POWER (W) | 40W |
| SYSTEM OUTPUT (LM) | 5200LM |
| EFFICACY (LM/W) | 130LM/W |
| CCT (K) | 3000K / 4000K / 5000K |
| CRI (Ra) | 90 |
| BEAM ANGLE | 110° DOWN / 120° UP |
| RATED LIFE (HRS) | 50 000HRS L90B10 |
| MAC ADAM STEP | SDCM <3 |
| DIMENSIONS | W:45 x L:1120 x H:75mm |

- CD / KLM
- C0 - C180
 - C90 - C270



E&OE MAY OCCUR

