



+ IP 20



LOA

5 YRS



PHYSICAL DATA

FEATURES

- Material: Aluminium and Polycarbonate
- Higher reflective efficiency with the ALANOD MIRO material
- Adjustable

MOUNTING

Track

OPTIONS & ACCESSORIES

- TRIAC, 0-10V, Dali dimming options available
- Special CCT options available for the lighting of meat, bread, fish, vegetables and clothing
- Glass accessories available

APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail

TECHNICAL DATA

LTL1517

LTL1525

LTL1533

TOTAL POWER (W)	20W	30W	36W
SYSTEM OUTPUT (LM)	1938 / 2245LM	2841 / 2970LM	3204 / 3486LM
EFFICACY (LM/W)	93 / 108	95 / 99	86 / 94
CCT (K)	3000 / 4000K	3000 / 4000K	3000 / 4000K
CRI (Ra)	80	80	80
BEAM ANGLE	15° / 14°	14°	14°
OPERATING VOLTAGE-VAC	220-240V	220-240V	220-240V
OPERATING TEMP °C	-20°C TO 50°C	-20°C TO 50°C	-20°C TO 50°C
SOURCE POWER (W)	17W	25W	33W
SOURCE OUTPUT (LM)	2290 / 2479LM	3201 / 3426LM	3851 / 4048LM
CURRENT (MA)	500MA	700MA	900MA
RATED LIFE (HRS)	50 000 HRS	50 000 HRS	50 000 HRS
ILLUM @ 1M (LUX)	10376 / 11743LX	15224 / 15892LX	17410 / 18458LX
FLICKER FACTOR	<4%	<4%	<4%
POWER FACTOR	≥0.9	≥0.9	≥0.9
R9 VALUE	11	12	12
UGR	<15 / <7	<15 / <7	<15 / <7
MAC ADAM STEP	3SDCM	3SDCM	3SDCM
DIMENSIONS	L:168 x W:243 x H:353mm	L:168 x W:243 x H:353mm	L:168 x W:243 x H:353mm

