

+ IP 20



LOA

5 YRS

ldt

F



PHYSICAL DATA

FEATURES

- Material: Aluminium and polycarbonate housing
- Reflector with clear glass and safety wire
- Driver built in track adapter
- Better heat dissipation with higher density aluminium alloy
- Higher reflective efficiency with the ALANOD MIRO material
- High quality LEDs to ensure excellent chromatic yield for strict colour rendering
- Adjustable

OPTIONS & ACCESSORIES

- Honeycomb, Barn Door, Glass accessories available
- TRIAC / DALI Dimming available

MOUNTING

Track


APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail

TECHNICAL DATA

LTL21

TOTAL POWER (W)	37W
SYSTEM OUTPUT (LM)	3292 / 3443 / 3703LM (LM @ 3000K)
EFFICACY (LM/W)	87 / 90 / 99
CCT (K)	3000 / 3500 / 4000K
CRI (Ra)	>80
BEAM ANGLE	15° / 20° / 43° / 53°
OPERATING VOLTAGE-VAC	220-240V
OPERATING TEMP °C	-20°C TO 50°C
SOURCE POWER (W)	32W
SOURCE OUTPUT (LM)	3795 / 4097 / 4325LM
CURRENT (MA)	900MA
RATED LIFE (HRS)	50 000 HRS
ILLUM @ 1M (LUX)	13564 / 14414/ 15662LX
FLICKER FACTOR	<4%
POWER FACTOR	≥0.9
R9 VALUE	8
UGR	<18
MAC ADAM STEP	3SDCM
DIMENSIONS	D:Ø96 x L:113 x W:208mm



CD / KLM

- C0 - C180
- C90 - C270

E&OE MAY OCCUR

