

- +IP 20
- 
- LOA
- 5 YRS
- ldt

**PHYSICAL DATA**


<p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>• Material: Aluminum</li> <li>• High performance with 130lm/W</li> <li>• High efficiency CRI90</li> <li>• CCT selectable</li> <li>• Dimming: On/Off DALI</li> </ul> <p><b>OPTIONS &amp; ACCESSORIES</b></p> <ul style="list-style-type: none"> <li>• Available in 3 lengths: 600mm / 1200mm / 1500mm</li> <li>• Available in 3 wattages: 20W / 40W / 50W</li> <li>• CCT: 3000K / 4000K / 5000K fixed &amp; CCT selectable</li> </ul>	<p><b>MOUNTING</b></p> <p>Track mounted</p> <p><b>APPLICATION AREAS</b></p> <p>Indoor, Commercial, Residential, Retail</p>
--	--

**TECHNICAL DATA**

**LTL39404030**

LAMP	LED
TOTAL POWER (W)	40W
SYSTEM OUTPUT (LM)	4800LM
EFFICACY (LM/W)	120 - 130LM/W
CCT (K)	4000K
CRI (Ra)	90
BEAM ANGLE	120°
RATED LIFE (HRS)	100 000HRS L80
	80 000HRS L90
MAC ADAM STEP	SDCM <3
DIMENSIONS	W:50 x L:1200 x H:70mm

- CD / KLM
- C0 - C180
- C90 - C270



E&OE MAY OCCUR

