



Colour: White

- +IP 20
- 
- LOA
- ✓ 5 YRS

### PHYSICAL DATA

#### FEATURES & ACCESSORIES

- Dimming interface: 0-10V(1-10V/10V PWM/RX), Push Dim
- Fully-protected plastic housing with removable end cover which is for convenient adjustments of length of drivers
- With soft-on and fade-in function, visually more comfortable
- Dimmable 0.1 -100% , Flicker-free, High frequency exemption level
- Automatic recognition of 0-10V, 1-10V input signal
- Ultra-low consumption of 0-10V ports
- High efficiency driver with innovative thermal management technology, intelligent power life protection

- Over-heat / Over voltage / Over load / Short circuit protection / Recover automatically
- Compliant with Safety Extra Low Voltage Standard
- Rated life: 50 000hrs

#### MOUNTING

- Subject to application
- Breathable environment

**APPLICATION AREAS:** LED Lighting Applications

### TECHNICAL DATA

#### LED75ADDALI12V

#### LED75ADDALI24V

#### LED150ADDALI12V

#### LED150ADDALI24V

MATERIAL	PLASTIC	PLASTIC	PLASTIC	PLASTIC
TYPE	DALI / PUSH DIM	DALI / PUSH DIM	DALI / PUSH DIM	DALI / PUSH DIM
OUTPUT POWER	75W	75W	150W	150W
INPUT VOLTAGE	220-240V	220-240V	220-240V	220-240V
OUTPUT VOLTAGE	DC 12V	DC 24V	DC 12V	DC 24V
AMPERE (A)	6.25A	3.12A	12.5A	6.25A
DIMENSIONS	L:293 x B:43 x H:30mm	L:293 x B:43 x H:30mm	L:352 x B:43 x H:30mm	L:352 x B:43 x H:30mm

#### 0-10V Connection



#### Push DIM Connection



0-100% dimming  
Short press to on/off, long press to dim.

Dimming interface priority: First 0-10V, next Push DIM.

