

+IP
44



LOA

✓
3 YRS

ldt

COLOUR
SELECTABLE

PHYSICAL DATA

FEATURES

- Construction: Die-cast aluminium powder coated body and trim, TPA rated polycarbonate diffuser, Steel spring clips with PVA covers
- Integrated switch allows selection between two wattages and four CCT's
- Complete with dimmable driver for use with selected leading and trailing edge dimmers
- Utilises high-quality LM80 tested SMD LEDs
- Slim die-cast body aids installation in shallow ceiling voids

OPTIONS & ACCESSORIES

- Suitable for switching by PIR, Microwave or Photocell
- Emergency options available for selection
- Extra-wide extension trim accessory available (RMP280TRIM-01)
- Surface mount accessory available (RMPSMK-01)

MOUNTING: Recessed / Surface using RMPSMK-01

APPLICATION AREAS

Indoor, Commercial, Retail, Hospitality, Public Buildings, Hospitals

TECHNICAL DATA


RMR1824X0-01

RMR3040X0-01

LAMP	LED	LED
TOTAL POWER (W)	18W & 24W	30W & 40W
SYSTEM OUTPUT (LM)	1850-2010 & 2360-2630LM	3210-3420 & 4020-4340LM
EFFICACY (LM/W)	98-109 & 92-105	107-115 & 101-111
CCT (K)	3000 & 4000 & 5000 & 6500K	3000 & 4000 & 5000 & 6500K
CRI (RA)	80	80
BEAM ANGLE	110°	110°
OPERATING VOLTAGE-VAC	220-240V	220-240V
OPERATING TEMP (°C)	-20°C to +40°C	-20°C to +40°C
RATED LIFE (HRS)	30 000HRS	30 000HRS
POWER FACTOR	0.9	0.9
ILLUM @ 1M (LUX)	690-750 & 870-980	1200-1270 & 1500-1610
IMPACT RATING (IK)	07	07
WEIGHT (KG)	0.97KG	1.01KG
DIMENSIONS	D:Ø227 x H:45mm	D:Ø227 x H:45mm
CUT OUT	D:Ø190mm	D:Ø190mm

CD / KLM

- C0 - C180
- C90 - C270



E&OE MAY OCCUR



Lights By Linea
Since (1990)

Cape Town | 48 Marine Dr, Paarden Eiland | T: +27 21 511 6116
info@lightsbylinea.com | www.lightsbylinea.com