

- + IP 20
- LOA
- 3 YRS
- ldt

PHYSICAL DATA

FEATURES

- Material: Aluminium
- The NIC is the most extensive product family in the FLUA collection, answering almost all your lighting requirements. The range includes round and square, recessed, round surface lights, adjustable and fixed options as well as square and rectangular plates allowing one to mount the NIC in a series of either one, two or three downlights
- Adjustable

OPTIONS & ACCESSORIES

- DALI, TRIAC DIM (dim to warm) and Dim 01/-10V dimming available

MOUNTING

Recessed


APPLICATION AREAS

Indoor, Commercial, Residential, Retail, Hospitality

TECHNICAL DATA

LF102025EA

LAMP	LED
TOTAL POWER (W)	6.7W
SYSTEM OUTPUT (LM)	477LM
CCT (K)	3000K
CRI (Ra)	90
BEAM ANGLE	20°
OPERATING VOLTAGE-VAC	220-240V
SOURCE POWER (W)	8W
SOURCE OUTPUT (LM)	623LM
CURRENT (MA)	350MA
FLICKER FACTOR	99.83HZ / 1.55%
WEIGHT	0.3KG
DIMENSIONS	D:φ75 x H:54.8mm
CUT OUT	D:φ67mm



- CD / KLM
- C0 - C180
- C90 - C270

E&OE MAY OCCUR

