

+ IP  
65



LOA

✓  
5 YRS

ldt

### PHYSICAL DATA

#### FEATURES

- Material: Stainless Steel
- The RAY is a low-power spotlight with a narrow beam angle
- Driver: On/Off

#### MOUNTING

Recessed


#### APPLICATION AREAS

Indoor, Commercial, Residential, Hospitality, Retail

### TECHNICAL DATA

### LF136511A

LAMP	LED
TOTAL POWER (W)	2.2W
SYSTEM OUTPUT (LM)	121LM
CCT (K)	3000 / 3500 / 4000K
CRI (Ra)	80
BEAM ANGLE	15° / 25°
OPERATING VOLTAGE-VAC	100-240V
SOURCE POWER (W)	4.2W
SOURCE OUTPUT (LM)	426LM
CURRENT (MA)	700MA
FLICKER FACTOR	1935.48HZ/ 6.15%
WEIGHT (KG)	0.09KG
DIMENSIONS	D:Ø37 x H:55mm
CUT OUT	D:Ø32mm



CD / KLM

- C0 - C180
- C90 - C270

E&OE MAY OCCUR



**Lights By Linea**  
Since (1990)

Cape Town | 48 Marine Dr, Paarden Eiland | T: +27 21 511 6116  
info@lightsbylinea.com | www.lightsbylinea.com