

- +IP 20
- 5 YRS
- ldt

PHYSICAL DATA

FEATURES

- Aluminium extrusion with PMMA Opal diffuser
- Built-In LED Driver
- Maintenance by removable gear tray
- Customizable lengths and shapes

OPTIONS & ACCESSORIES

- EME 1hr or EME 3hr available
- DALI, Occupancy Control, Daylight Harvesting, Time Switch Control and Bluetooth options available

- Smart-light control available

MOUNTING

Suspended, Surface, Track

APPLICATION AREAS

Indoor, Commercial, Residential, Retail, Hospitality

PLEASE NOTE


Dimmable drivers may be remote

TECHNICAL DATA

LLEDSW1-3K

LLEDSW1-4K

LAMP	LED	LED
TOTAL POWER (W)	20 / 28 / 41W per m	20 / 28 / 41W per m
SYSTEM OUTPUT (LM)	3170LM - 6550LM	3170LM - 6550LM
EFFICACY (LM/W)	182 / 174 / 165	182 / 174 / 165
CCT (K)	3000K	4000K
CRI (Ra)	>80	>80
BEAM ANGLE	120°	120°
OPERATING VOLTAGE-VAC	230V 50Hz	230V 50Hz
SOURCE POWER(W) SOURCE	22.5 - 46W per m	22.5 - 46W per m
OUTPUT (LM)	3607 / 4490 / 6865LM	3805 / 5380 / 7322 LM
OPERATING TEMP °C	-20°C TO 45°C	-20°C TO 45°C
TC CASE MAX TEMP °C	70 - 90°C	70 - 90°C
CURRENT (MA)	250MA-500MA	250MA-500MA
RATED LIFE (HRS)	50 000HRS	50 000HRS
POWER FACTOR	0.95	0.95
LUMEN MAINTENANCE	L90-B10	L90-B10
FLICKER FACTOR	<5%	<5%
MAC ADAM STEP	3 SDCM	3 SDCM
DIMENSIONS	W:50 x H:75mm	W:50 x H:75mm



CD / KLM

C0 - C180

C90 - C270

E&OE MAY OCCUR

