

+IP
20



✓
3 YRS

ldt

PHYSICAL DATA

FEATURES

- Aluminium extrusion with clip-in PMMA Opal diffuser
- Drivers to be installed remotely
- Customizable lengths and shapes

MOUNTING

Suspended or Surface

OPTIONS & ACCESSORIES

- EME 1hr or EME 3hr available
- DALI, Occupancy Control, Daylight Harvesting, Time Switch Control and Bluetooth options available

APPLICATION AREAS


Indoor, Commercial, Residential, Retail, Hospitality

TECHNICAL DATA

LLEDSW2-3K

LLEDSW2-4K

LAMP	LED	LED
TOTAL POWER (W)	20 / 28 / 41W per m	20 / 28 / 41W per m
SYSTEM OUTPUT (LM)	3607 / 4490 / 6865LM	3805 / 5280 / 7322LM
EFFICACY (LM/W)	182 / 174 / 165	192 / 186 / 176
CCT (K)	3000K	4000K
CRI (Ra)	>80	>80
BEAM ANGLE	120°	120°
OPERATING VOLTAGE-VAC	220-240V	220-240V
OPERATING TEMP °C	-20°C TO 35°C	-20°C TO 35°C
CURRENT (MA)	250 / 350 / 500MA	250 / 350 / 500MA
RATED LIFE (HRS)	50 000HRS	50 000HRS
POWER FACTOR	0.95	0.95
LUMEN MAINTENANCE	L90-B10	L90-B10
FLICKER FACTOR	<5%	<5%
MAC ADAM STEP	3 SDCM	3 SDCM
DIMENSIONS	W:50 x H:35mm	W:50 x H:35mm



CD / KLM

● C0 - C180

● C90 - C270

E&OE MAY OCCUR



Lights By Linea
Since (1990)

Cape Town | 48 Marine Dr, Paarden Eiland | T: +27 21 511 6116
info@lightsbylinea.com | www.lightsbylinea.com