

+IP
20



5 YRS

ldt

PHYSICAL DATA

FEATURES

- Material: Aluminium extrusion with opal UV stabilized clip-in PMMA diffuser
- Innovative thermal management employing passive cooling
- Impact protection class IK8
- Driver to be installed remotely
- Customized lengths and shapes

- DALI, Occupancy Control, Daylight Harvesting, Time Switch Control and Bluetooth options available

MOUNTING

Recessed

APPLICATION AREAS

Indoor, Commercial, Residential, Retail, Hospitality

OPTIONS & ACCESSORIES

- EME 1hr or EME 3hr available


TECHNICAL DATA

LLEDSW4

LAMP	LED
TOTAL POWER (W)	20 / 28 / 41W per m
SYSTEM OUTPUT (LM)	3607 / 4490 / 6865LM @3000K 3805 / 5280 / 7322LM @4000K
EFFICACY (LM/W)	182 / 174 / 165 @3000K 192 / 186 / 176 @4000K
CCT (K)	3000K / 4000K
CRI (Ra)	>80
BEAM ANGLE	120°
OPERATING VOLTAGE-VAC	220-240V
OPERATING TEMP °C	-20°C TO 35°C
CURRENT (MA)	250 / 350 / 500MA
RATED LIFE (HRS)	50 000HRS
POWER FACTOR	0.95
LUMEN MAINTENANCE	L90-B10
FLICKER FACTOR	<5%
MAC ADAM STEP	3 SDCM
DIMENSIONS	W:65 x H:35mm



- CD / KLM
- C0 - C180
 - C90 - C270



E&OE MAY OCCUR



Lights By Linea
Since (1990)

Cape Town | 48 Marine Dr, Paarden Eiland | T: +27 21 511 6116
info@lightsbylinea.com | www.lightsbylinea.com