

- +IP 20
- 5 YRS
- 

### PHYSICAL DATA

#### FEATURES

- Innovative thermal management employing passive cooling
- Protection class IK8
- Diffuser material Opal UV stabilized PMMA
- Colour consistency (SDCM) is Mac Adams <3
- Maintenance by removable gear tray
- Built-in LED driver

- Dimmable options available
- Smart-light control available
- Intelligent programmable options ie DALI, Casambi, sensor occupancy, daylight harvesting

#### MOUNTING

Recessed

#### APPLICATION AREAS

Indoor, Commercial, Residential, Retail, Hospitality


#### OPTIONS & ACCESSORIES

- EME 1hr or EME 3hr available

### TECHNICAL DATA

### LLEDSW5

LAMP	LED
TOTAL POWER (W)	20 / 28 / 41W per m
SYSTEM OUTPUT (LM)	3607 / 4490 / 6865LM @3000K 3805 / 5280 / 7322LM @4000K
EFFICACY (LM/W)	182 / 174 / 165 @3000K 192 / 186 / 176 @4000K
CCT (K)	3000K / 4000K
CRI (Ra)	>80
BEAM ANGLE	120°
OPERATING VOLTAGE-VAC	220-240V
OPERATING TEMP °C	-20°C TO 35°C
CURRENT (MA)	250 / 350 / 500MA
RATED LIFE (HRS)	50 000HRS
POWER FACTOR	0.95
LUMEN MAINTENANCE	L90-B10
FLICKER FACTOR	<5%
MAC ADAM STEP	3 SDCM
DIMENSIONS	W:68 x H:75mm



E&OE MAY OCCUR

