



PHYSICAL DATA

FEATURES

- Material: UV stabilized polycarbonate base with stainless steel 316 clips and UV stabilized polycarbonate frosted lens with built-in optics
- The TVPA-Range is ideal for industrial use where moisture and dust particles are active in the atmosphere
- Easy installation and no need to drill through the fitting
- Energy-saving, Non-corrosive, SMD LED gear tray reflector
- The SMD LED gear-tray is interchangeable if so required for ease of maintenance

OPTIONS & ACCESSORIES

- All the fittings are available with motion sensor and emergency back-up units

MOUNTING:

Surface

APPLICATION AREAS

Indoor, Commercial, Residential, Retail, Hospitality

TECHNICAL DATA

TVPA212/LED

TVPA224/LED

TVPA230/LED

LAMP	LED	LED	LED
TOTAL POWER (W)	2 x 12W	2 x 24W	2 x 30W
SYSTEM OUTPUT (LM)	2400LM	4800LM	6000LM
CCT (K)	4100K	4100K	4100K
CRI (RA)	80	80	80
OPERATING VOLTAGE-VAC	220-240V	220-240V	220-240V
CLIPS PER SIDE	3	5	6
DIMENSIONS	L:632 x W:85 x D:71mm	L:1232 x W:85 x D:71mm	L:1532 x W:85 x D:71mm



E&OE MAY OCCUR



Lights By Linea
Since (1990)

Cape Town | 48 Marine Dr, Paarden Eiland | T: +27 21 511 6116
info@lightsbylinea.com | www.lightsbylinea.com