



LIGHTS BY
LINEA

EST. 1990

RETAIL

BROCHURE

Our Mission Statement



Lighting Beyond Illumination

We craft innovative lighting design solutions that don't just light spaces — they transform them.

From concept to specification, we ensure the right product for every project, achieving your vision with precision and style.

Competitive pricing. On-time delivery. Uncompromising quality.

Technical Information & Symbol Descriptions



CEILING

PENDANTS



LBLP29


Wattage:
18/26/32/41W

Beam angle:
35°/50°

CCT:
3000/3500/4000K

System Output:
2250LM @4000K 18W
3855LM @4000K 26W
4615LM @4000K 32W
5605LM @4000K 41W

Dimensions:
Ø32x203mm



LBLP27

Wattage:
60/93/186W

Beam angle:
120°

CCT:
3000/4000K

System Output:
4264LM @4000K 60W
6720LM @4000K 93W
13520LM @4000K 186W

Dimensions:
Ø1000x50x80mm
Ø1500x50x80mm
Ø3000x50x80mm



LP01

Wattage:
2x25W

Beam angle:
27°

CCT:
3500/4000K

System Output:
2x2940LM @3500K
2x2970LM @4000K

Dimensions: LxWxH
382x228x136mm



LP05

Wattage:
20/30W

Beam angle:
15°/24°/44°/59°

CCT:
3500/4000K

System Output:
2185LM @3500K 20W
2245LM @4000K 30W

Dimensions:
Ø116x177mm



LP06


Wattage:
72W

Beam angle:
27°

CCT:
3500K

System Output:
7350LM @3500K

Dimensions:
Ø680x100mm



CEILING LIGHTS



LSD09

Wattage:
32/66W

Beam Angle:
108°/111°

CCT:
3500/4000K

System Output:
3468LM @3500K 32W
7250LM @3500K 66W
3529LM @4000K 32W
7577LM @4000K 66W

Dimensions:
Ø480x100mm
Ø680x100mm



3CCT PANEL

Wattage:
18/24/32W

Beam Angle:
120°

CCT: 3CCT
3000/4000/6000K

System Output:
1700LM @3000K 18W
2400LM @3000K 24W
3200LM @3000K 32W

Dimensions:
Ø230x25mm
Ø300x25mm
Ø400x25mm



LSD01

Wattage:
20/30W

Beam angle:
15°/ 44°

CCT:
3500/4000K

System Output:
1974LM @3500K 20W
2867LM @3500K 30W
2245LM @4000K 20W
2970LM @4000K 30W

Dimensions:
Ø117x176mm



LSS07

Wattage:
40W

Beam angle:
45°


CCT:
3500K

System Output:
4400LM @3500K

Dimensions:
Ø100x99mm



3 CIRCUIT TRACK



N04728


Dimensions: LxWxH
1000x35x35mm




N04718
TRACK CLIP
WIRE/ROD




N04720420
L-CONNECTOR



N04725520
FLEXIBLE
CONNECTOR




N0471120
END COVER



N04720520
MIDDLE
CONNECTOR



N04726420
FLEX 60
CONNECTOR




N04720120
X-CONNECTOR



N04720620
LEFT END FEED



N047128
CEILING PROFILE




N04720220
T-CONNECTOR L



N04720720
RIGHT END FEED



N04776
TRACK CLIP



N04730320
T-CONNECTOR R




N04720920
MINI
CONNECTOR



N047286
SUSPENSION
KIT

3-CIRCUIT TRACK LIGHTS



LTL21
 Wattage: 37W
 Beam angle: 15°/43°/53°
 CCT: 3500/4000K
 System Output: 3443LM @3500K
 Dimensions: DxLxW
 Ø96x113x208mm



LTL37
 Wattage: 40W
 Beam angle: 15°/24°/60°
 CCT: 3500K
 System Output: 3690LM @3500K
 Dimensions: Ø100x125mm




LTL38
 Wattage: 30W
 Beam angle: 27°-50° zoomable
 CCT: 3000/4000K
 System Output: 2264-2855LM @3000K
 Dimensions: Ø80x170mm



ZEN EVO 31W
 Wattage: 31W
 Beam angle: 16°/40°/60°
 CCT: 3500K/4000K
 System Output: 4000LM @3500K
 Dimensions: Ø104x222mm



ZEN EVO 40W
 Wattage: 40W
 Beam angle: 16°/40°/60°
 CCT: 3500K/4000K
 System Output: 4800LM @3500K
 Dimensions: Ø104 x 222mm



LTL31
 Wattage: 50W
 Beam angle: 90°
 CCT: 4000K
 System Output: 8000LM @4000K
 Dimensions: LxWxH
 1493x60x10mm



LTL32
 Wattage: 50W
 Beam angle: 90° wide
 CCT: 4000K
 System Output: 6250LM @4000K
 Dimensions: LxWxH
 1493x60x12mm



LTL33
 Wattage: 50W
 Beam angle: 30° sharp
 CCT: 4000K
 System Output: 7000LM @4000K
 Dimensions: LxWxH
 1493x120x12mm



LTL39
 Wattage: 17/34W
 Beam angle: 60°/90°
 CCT: 3000/4000K
 System Output: 2855LM @4000K 17W
 5710LM @4000K 34W
 Dimensions: LxWxH
 578x60x80mm
 1138x60x80mm



COMMERCIAL

LINEAR LIGHTING




LSL04
 Wattage: 30/38/60W
 Beam angle: 90°/120°
 CCT: 4000K
 System Output: 3000LM @4000K 30W
 4900LM @4000K 38W
 6500LM @4000K 60W
 Dimensions: LxWxH
 1727x62x27mm
 1153x62x27mm
 350x288x27mm




LLED5W1
 Wattage: 20/28/41W/m
 Beam angle: 120°
 CCT: 3000/4000K
 System Output: 3607LM @4000K 20W/m
 4490LM @4000K 28W/m
 6865LM @4000K 41W/m
 Dimensions: LxWxH
 *x 50 x 75mm



LSL06
 Wattage: 30/60/75W
 Beam angle: 120°
 CCT: 4000K
 System Output: 4200LM @4000K 30W
 8300LM @4000K 60W
 10000LM @4000K 75W
 Dimensions: LxWxH
 500x50x35mm
 1200x50x35mm
 1500x50x35mm



LSL07
 Wattage: 30/60W
 Beam angle: 120°
 CCT: 4000K
 System Output: 3300LM @4000K 30W
 6500LM @4000K 60W
 Dimensions: LxWxH
 600x50x50mm
 1200x50x50mm



LEDRAIL 4100 EASY
 Wattage: 45/75W
 Beam angle: 90°
 CCT: 3000/4000/5000K
 System Output: 6834LM @4000K 45W
 11390LM @4000K 75W
 Dimensions: LxWxH
 1680x56x56mm
 2800x56x56mm




COMMERCIAL & ARCHITECTURAL



LEDRAIL 4100 PROFESSIONAL
 Wattage: 51/84W
 Beam angle: 90°
 CCT: 3000/4000/5000K
 System Output: 7752LM @4000K 51W
 12920LM @4000K 84W
 Dimensions: LxWxH
 1680x56x56mm
 2800x56x56mm



PUCK SEAMLESS
 Wattage: 52/116W
 Beam angle: 160°
 CCT: 4000/5000K
 System Output: 6500LM @4000K 52W
 13000LM @4000K 116W
 Dimensions: LxWxH
 1200x36x70mm
 2400x36x70mm



PUCK 40X43
 Wattage: 32/64W
 Beam angle: 120°
 CCT: 4000/5000K
 System Output: 4000LM @4000K 32W
 8000LM @4000K 64W
 Dimensions: LxWxH
 1200x36x70mm
 2400x36x70mm




PUCK 70X36
 Wattage: 52/104W
 Beam angle: 160°
 CCT: 4000/5000K
 System Output: 6000LM @4000K 52W
 12000LM @4000K 104W
 Dimensions: LxWxH
 1200x36x70mm
 2400x36x70mm



Project: Tom Tailor

RECESSED

COMMERCIAL & ARCHITECTURAL



LLEDSW4


Wattage:
20/28/41W/m

Beam angle:
120°

CCT:
3000/4000K

System Output:
3805LM @4000K 20W/m
5280LM @4000K 28W/m
7322LM @4000K 41W/m

Dimensions: LxWxH
*x65x35mm



LLEDSW5

Wattage:
20/28/41W/m

Beam angle:
120°

CCT:
3000/4000K

System Output:
3805LM @4000K 20W/m
5280LM @4000K 28W/m
7322LM @4000K 41W/m

Dimensions: LxWxH
*x68x75mm



Project RMS Shoptitters / Photography: Anagrophy

PANEL LIGHTS

COMMERCIAL & ARCHITECTURAL



LLEDP1340


Wattage:
42W

Beam angle:
110°

CCT:
3500/4000K

System Ouput:
5200LM @4000K

Dimensions: LxWxH
595x595x32mm



LLEDP1341


Wattage:
42W

Beam angle:
110°

CCT:
4000K

System Ouput:
5460LM @4000K

Dimensions: LxWxH
1195x295x32mm



LLEDP1355

Wattage:
55.5W

Beam angle:
90°

CCT:
4000K

System Ouput:
7613LM @4000K

Dimensions: LxWxH
1195x595x32mm



LLEDP14404031


Wattage:
40W

Beam angle:
90°

CCT:
4000K

System Ouput:
3960LM @4000K

Dimensions: LxWxH
595x595x32mm



LLEDP14424031


Wattage:
40W

Beam angle:
90°

CCT:
4000K

System Ouput:
3960LM @4000K

Dimensions: LxWxH
1195x295x32mm



LLEDP1460W

Wattage:
56W

Beam angle:
90°

CCT:
4000K

System Ouput:
5712LM @4000K

Dimensions: LxWxH
1195x595x32mm



RECESSED DOWNLIGHTS

COMMERCIAL



LRD02

Wattage:
15W

Beam angle:
42°

CCT:
3500/4000K

System Ouput:
1749LM @4000K

Dimensions:
Ø157x119mm



LRD03

Wattage:
25W

Beam angle:
60°

CCT:
3500/4000K

System Ouput:
1984LM @4000K

Dimensions:
Ø180x119mm



LRD04

Wattage:
7W

Beam angle:
28°

CCT:
3500/4000K

System Ouput:
594LM @4000K

Dimensions:
Ø85x105mm



LRD09

Wattage:
25W

Beam angle:
40°/60°

CCT:
3500/4000K

System Ouput:
1788LM @4000K

Dimensions:
Ø165x155mm



LRD10


Wattage:
27/33W

Beam angle:
27°/42°

CCT:
3000/4000K

System Ouput:
2970LM @4000K 27W
3486LM @4000K 33W

Dimensions:
Ø180x110mm



LRD12


Wattage:
27W

Beam angle:
27°

CCT:
3500/4000K

System Ouput:
2970LM @4000K

Dimensions: LxWxH
176x176x138mm



LRD122

Wattage:
2 x 30W

Beam angle:
27°

CCT:
3500/4000K

System Ouput:
2 x 2970LM @4000K

Dimensions: LxWxH
176x176x138mm



LRD13

Wattage:
25W

Beam angle:
27°

CCT:
3500/4000K

System Ouput:
2970LM @4000K

Dimensions:
Ø180x173mm



LRD14

Wattage:
24W

Beam angle:
24°

CCT:
3500/4000K

System Ouput:
2970LM @4000K

Dimensions:
Ø116.5x171mm



LRD142

Wattage:
2 x 25W

Beam angle:
24°

CCT:
3500/4000K

System Ouput:
2 x 2970LM @4000K

Dimensions: DxWxH
Ø116.5x335x171mm



LRD16

Wattage:
25W

Beam angle:
20°/37°

CCT:
3500/4000K

System Ouput:
2550LM @4000K

Dimensions: DxWxL
Ø103x155x122mm



LRD20S

Wattage:
25W

Beam angle:
78°

CCT:
3500/4000K

System Ouput:
2041LM @4000K

Dimensions: LxWxH
180x130x108mm



LRD28

Wattage:
12W

Beam angle:
120°

CCT: 3CCT
3000/4000/6000K

System Output:
1380LM @3000K

Dimensions:
Ø75x42mm



LRD71

Wattage:
10/18/24W

Beam angle:
120°

CCT: 3CCT
3000/4000/6000K

System Output:
1000LM @3000K 10W
1800LM @3000K 18W
2400LM @3000K 24W

Dimensions:
Ø140x28mm
Ø190x28mm
Ø230x28mm



LRD72

Wattage: selectable
18/24W or 26/35W

Beam angle:
60°

CCT: 3CCT
3000/4000/6000K

System Output:
2160LM @3000K 18W
2880LM @3000K 24W
3120LM @3000K 26W
4200LM @3000K 35W

Dimensions:
Ø165x60mm
Ø220x66.5mm



COMMERCIAL



LRD74

Wattage:
10/18/24W

Beam angle:
90°

CCT:
3000/4000K

System Output:
1000LM @4000K 10W
1800LM @4000K 18W
2400LM @4000K 24W

Dimensions:
Ø113x49mm
Ø174x65mm
Ø232x77mm



LRS07

Wattage:
40W

Beam angle:
15°/36°/60°

CCT:
3000/4000K

System Ouput:
4560LM @3000K
5000LM @4000K


Dimensions:
Ø100x99mm



Project: Jigrow, V&A Waterfront


STRIPS

PROFILES & DIFFUSERS




LBLEXTA4

Dimensions: LxWxH
2000x23.1x7mm



LBLEXTA6

Dimensions: LxWxH
2000x17.5x7mm




LBLEXTA10

Dimensions: LxWxH
2000x23x10mm




LBLEXTA11

Dimensions: LxWxH
2000x17.5x15mm




LBLEXTA12B

Dimensions: LxWxH
2000x44x35mm




LBLEXTA13

Dimensions: LxWxH
2000x16x16mm




LBLEXTA15

Dimensions: LxWxH
2000x24.5x14.5mm




LBLEXTA18

Dimensions: LxWxH
2000x10x10mm



LBLEXTA48

Dimensions: LxWxH
2000x35x35mm



LBLEXTA54

Dimensions: LxWxH
2000x15x6.27mm



LBLEXTACLIP**
END CAPS



LBLEXTAEC**
CLIPS

24V LED STRIPS



LBLFLEX5

Wattage:
5W

CCT:
3000K

System Output:
512LM @3000K

Cut length:
50mm



LBLFLEX10

Wattage:
10W

CCT:
3000/4000K

System Output:
880LM @3000K
989LM @4000K

Cut length:
50mm




LBLFLEX14.4

Wattage:
14.4W

CCT:
3000/3500/4000K

System Output:
2154LM @3000K
2278LM @3500K
2947LM @4000K

Cut length:
50mm




LBLFLEX23

Wattage:
23W

CCT:
3000/3500/4000K

System Output:
2117LM @3000K
2241LM @3500K
2419LM @4000K

Cut length:
25mm



LBLFLEX14.4
RGB

Wattage:
14.4W

CCT: (All colors RGB @100%)
RGB 39015.80K

System Output:
620LM

Cut length:
100mm




LBLFLEX18
DTW224

Wattage:
18W

CCT: (Dim to warm)
1800-3000K

System Output:
1529LM @3000K

Cut length:
62.5mm



LBLFLEX-
19.2CWRGB

Wattage:
19.2W


CCT:
RGBW 3000/4000K

System Output:
1163LM @3000K
1287LM @4000K






Cut length:
62.5mm








COMMERCIAL & ARCHITECTURAL



 	 	 	 	 
LBLNEON6	LEDNEON10	MAGICNEONRGB	MAGICNEON SINGLE COLOR	3DSILICONE-NEON
Wattage: 6W	Wattage: 9.6W	Wattage: 6.4/19.2W/m	Wattage: 16W/m	Wattage: 10W
CCT: 3000-3500K	CCT: 2700/3000/4000/ 6000K	CCT: RGB	CCT: 3000/4000K	CCT: 3000/4000/6000K
System Ouput: 348LM @3000K	System Ouput: 500LM @2700K	System Ouput: 108LM @6.4W/m 696LM @19.2W/m	System Ouput: 1457LM @3000K 1466LM @4000K	System Ouput: 700LM @3000K 730LM @4000/6000K
Cut length: 25mm	Cut length: 50mm	Cut length: 35.7/41.66mm	Cut length: 35.7mm	Cut length: 50mm

DRIVERS & ACCESSORIES

				
LED(75/150) TD24	LED(75/150) CTDALI24V	LED(75/150) ADDALI24V	LBL(75/150) WNWP24VDD	LBL(75/150) WNWP24VTD
Wattage: 75/150W	Wattage: 75/150W	Wattage: 75/150W	Wattage: 75/150W	Wattage: 75/150W
Input voltage: 220-240V	Input voltage: 220-240V	Input voltage: 0-10V/1-10V/ 10V PWM	Input voltage: 100-240V	Input voltage: 220-240V
Ouput voltage: DC24V	Ouput voltage: DC24V	Ouput voltage: DC24V	Ouput voltage: DC24V	Ouput voltage: DC24V
Dimensions: LxWxH 273x57x37mm 293x43x30mm	Dimensions: LxWxH 273x57x37mm 293x43x30mm	Dimensions: LxWxH 293x43x30mm 352x43x30mm	Dimensions: LxWxH 213x54x33mm 206x75x41mm	Dimensions: LxWxH 213x54x33mm 260x78.3x45mm

			
LBL(60/120/150) NWP12V	LBL(60/100/150) NWP	LBL(75/150) WP12VJ	LBL(60/150) WP24V
Wattage: 60/120/150W	Wattage: 60/100/150W	Wattage: 75/150W	Wattage: 60/150W
Input voltage: 100-250V	Input voltage: 100-250V	Input voltage: 170-250V	Input voltage: 90-370V
Ouput voltage: DC12/24V	Ouput voltage: DC12/24V	Ouput voltage: DC12V	Ouput voltage: DC12/24V
Dimensions: LxWxH 110x78x35mm 160x98x38mm	Dimensions: LxWxH 110x78x35mm 160x98x38mm	Dimensions: LxWxH 213x54x33mm 244x71x45mm	Dimensions: LxWxH 148x40x30mm 162.5x42.5x32mm 191x63x37.5mm
			
LBL150WNW-P24VSN	LBL75WNW-P24VSN	LBL150WNWP24	
Wattage: 150W	Wattage: 75W	Wattage: 150W	
Input voltage: 220-240V	Input voltage: 180-240V	Input voltage: 220-240V	
Ouput voltage: 24V	Ouput voltage: 24V	Ouput voltage: 24V	
Dimensions: LxWxH 320x30x18.2mm	Dimensions: LxWxH 304.6x30x16.7mm	Dimensions: LxWxH 336.6x30x18.2mm	





LEDCTMM1

Wattage:
108/216W

Input voltage:
12-24V

Ouput voltage:
DC12/24V

Dimensions: LxWxH
104x60x90mm




LEDCTMM8

Wattage:
100/240/480W

Input voltage:
220-240V

Ouput voltage:
DC5/12/24V

Dimensions: LxWxH
104x58x90mm



LBLPANEX5

Input voltage:
100-240V

Ouput voltage:
DC5/12/24V

Dimensions: LxWxH
86x86x36mm



LBLPANEX8S-8RGBW

Input voltage:
100-240V

Ouput voltage:
DC5/12/24V

Dimensions: LxWxH
86x86x36mm



LBLPANBLEUB-1DIM

Input voltage:
120-240V

Ouput voltage:
DC5/12/24V

Dimensions: LxWxH
451x75x30mm



LBLPANBLEUB-84RGBW

Input voltage:
120-240V

Ouput voltage:
DC5/12/24V

Dimensions: LxWxH
451x75x30mm




**P410ARC
SUSPENSION
CABLES**



**LBLMSWITCH
MAGNETIC
SWITCH**



**CD_IR-MS
MINI PIR SWITCH**



**LBLQUICKCON-
NECTM/F
QUICK CONNEC-
TORS**

HIGHBAYS



DLHB0152CCT

Wattage:
110/150/200W

Beam angle:
90°

CCT: 3CCT
4000/5000/5700K

System Output:
16500LM @4000K 110W
21750LM @4000K 150W
28000LM @4000K 200W

Dimensions:
Ø305x181mm



LINEAR BAY XT

Wattage:
87/130W

Beam angle:
30°/60°/ 90°

CCT:
3000/4000/5000K

System Ouput:
13800LM @3000K 87W
20800LM @3000K 130W

Dimensions: LxW
1250x110mm
1700x110mm



UTILITY LIGHTS



LLEDVP05

Wattage:
20-35W

Beam angle:
120°

CCT: 3CCT
4000/5000/6500K

System Output:
3750LM @4000K 20W
5250LM @4000K 35W

Dimensions: LxWxH
1200x80x72mm
1500x80x72mm



LLEDB11

Wattage:
36/55/75W

Beam angle:
120°

CCT:
4000K

System Output:
4000LM @4000K 36W
6000LM @4000K 55W
9500LM @4000K 75W

Dimensions: LxWxH
1133x63x76mm
1415x63x76mm
1697x63x76mm



LLEDTP03

Wattage:
50W

Beam angle:
120°

CCT:
4000K

System Output:
5500LM @4000K

Dimensions: LxWxH
1500x50x55mm



BH130

Wattage:
15W

Beam angle:
120°

CCT:
4000K

System Ouput:
1800LM @4000K

Dimensions:
Ø160x60mm



EMG

EMERGENCY EXIT SIGNS



LEMGE03

Voltage:
230V

Duration:
3hours

Dimensions: LxWxH
430x45x215mm



LEMGE04


Wattage:
15W

Duration:
2hours

Dimensions: LxWxH
310x65x310mm

COMMERCIAL & ARCHITECTURAL

EMG LIGHTS



RCN4STO-01

Wattage:
2.4W

Beam angle:
120°

CCT:
6500K

System Output:
320LM @6500K

Dimensions:
Ø75x30mm

EMG BATTERY PACKS



LEDUNIVERSE

Voltage:
110-250V

Charging time:
24H

Max casing temp:
70°C

Dimensions: LxWxH
170x45x35mm



LEDUNIVERSEDELTA

Voltage:
110-253V

Charging time:
24H

Max casing temp:
70°C

Dimensions: LxWxH
170x45x35mm

COMMERCIAL & ARCHITECTURAL



SENSORS

COMMERCIAL & ARCHITECTURAL



EBDSM

Voltage:
230V

Operating temp:
-10 to 35°C

Time-out range:
10s-99Min

Dimensions:
Ø49x50mm



EBDSPIR

Voltage:
230V

Operating temp:
-10 to 35°C

Time-out range:
10s-99Min

Dimensions:
Ø76x69mm



EBMPIR-MB

Voltage:
230V

Operating temp:
-10 to 50°C

Time-out range:
10s-99Min

Dimensions: LxWxH
114x28x38mm



GEFL

Voltage:
230V

Operating temp:
-10 to 35°C

Time-out range:
10s-30Min

Dimensions:
Ø76x69mm



GESM

Voltage:
230V

Operating temp:
-10 to 35°C

Time-out range:
10s-30Min

Dimensions:
Ø96.5x50mm



DESIGN & TECHNICAL CERTAINTY

