



+IP
20



LOA

✓
5 YRS

ldt



PHYSICAL DATA

FEATURES

- Material: Die-cast aluminium
- Circular, modern design, tiltable and rotating downlight with 'chip on board' and separated NL Power LED electronic ballast for optimal lifetime and light flow performance
- High-quality reflectors with four different beam spreads
- Lamp housing of die-cast aluminium for optimal cooling and low weight
- Control: On/Off
- Adjustable with 60° tilt and 360° rotation capability

OPTIONS & ACCESSORIES

- Available in various lumen packages and beam angles

MOUNTING

Recessed

APPLICATION AREAS

Indoor, Commercial, Residential, Retail, Hospitality

TECHNICAL DATA

N3069220358020

TOTAL POWER (W)	40W
SYSTEM OUTPUT (LM)	4447LM
CCT (K)	3500K
CRI (Ra)	>90
BEAM ANGLE	14° / 27° / 38° / 56°

OPERATING VOLTAGE-VAC	220-240V
RATED LIFE (HRS)	50 000HRS
LUMEN MAINTENANCE	L80B10 @ 50 000HRS
WEIGHT (KG)	0.9KG
DIMENSIONS	D:Ø176 x H:135mm
CUT OUT	D:Ø165mm

Spot		Medium		Flood		Wide Flood	
14°		27°		38°		56°	
m	Ø	m	Ø	m	Ø	m	Ø
1.0	0.25	1.0	0.48	1.0	0.69	1.0	1.07
2.0	0.49	2.0	0.95	2.0	1.39	2.0	2.14
3.0	0.74	3.0	1.43	3.0	2.08	3.0	3.22



LIGHTS BY
LINEA

EST. 1990

DESIGN & TECHNICAL CERTAINTY

E&OE MAY OCCUR